

FMLS SERIES

Residential Lighting


WESTGATE

THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

FMLS-R5-MCT5-DT

5" SNAP FLUSH-MOUNT DISK 5CCT

MCT Multi Color Temperature (Selectable)




Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



5" x 1 3/5"

Features

- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Performance
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Die-cast Aluminum. Powder-Coated
- 5-Year Warranty
- 1" Deep

Technical Specifications

Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 11W
- Efficacy: 62 LPW

Mechanical:

- White Finish
- Stainless Steel Test Button with Integrated Indicator Light
- Die-cast Aluminum. Powder-Coated
- Maximum Ambient Temperature: 32°F to 104°F
- 5-Year Warranty
- Wet Location

Lighting:

- Multi CCT (Selectable Switch on Driver)
- LED: Edge Lit LED Technology
- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- 4W, 60V, 2500mAh Li-ion Battery for Minimum 90 Total Lumens: Min. 680LM ~ Max. 805LM
- Color Temperatures: 2700/3000/3500/4000/5000K
- Color Rendering Index: CRI ≥ 90
- Beam angle: 120°
- Rated life: 50,000 hrs

Applications:

- Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:

• 14W | 900LM | FMLS-R7-MCT5-DT

• 20W | 1300LM | FMLS-R9-MCT5-DT

• 25W | 1650LM | FMLS-R11-MCT5-DT





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-07182022

Photometrics: FMLS-R5-MCT5-DT



BUG Rating: B0-U1-G0




Simulation Based on 4000K Area 30'x 30' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: FMLE-R5-MCT5-E26

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
FMLS-R5-MCT5-DT	11W	120V	Min.680LM ~ Max. 805LM	2700K 3000K 3500K 4000K 5000K	B0-U1-G0	62

Sample Ordering

Model	Size	Color Temp.	Dimming
FMLS	-	R5	-
MCT5	-	DT	

DT = TRIAC Dimming

