GPH SERIES Outdoor Lighting

GPH-12-40W-MCTP-BR
MODERN TOP-HAT POST-TOP AREA LIGHT WITH INDIRECT LIGHT SOURCE


MITP Multi Color Temperature & Multi Power/Wattage (Selectable)



GPH is a classic led post-top light for illuminating yards, parks, parking areas, and other public outdoor spaces. It is wellshielded and delivers clear white light, creating a pleasant ambiance while enabling good energy savings. Symmetrical light distribution is designed for area lighting. It is made of highquality, durable materials and can be directly mounted on a Ø 60 mm & Ø 76 mm post. A glare shield is an accessory that makes light-dark sky friendly, no upward light.



Customer Name: Project Name: Note: Type:



19 8/9"(H) x 22"(D)

eatures

- Powder Coating: Bronze
- Aluminum Housing & PC Lens

- 7-Year Warranty
- Multi-CCT & Power: Switch Is Inside Fixture

Technical Specifications

Electrical:

Voltage: 120-277V AC 60Hz Wattage: 12W/20W/30W/40W

Power Factor: >0.90 Efficacy: 100LM/W

Mechanical:

- Aluminum Housing & PC Lens
- Powder Coating: Bronze
- Operating Temperature: -22°F to 122°F
- IP66 Suitable For Wet Location
- 7-Year Warranty

Lighting:

- Multi-CCT & Power: Switch Is Inside Fixture
- LED: LED 3030
- Total Lumens: 4000LM Max.
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 85°
- Rated Life: 70,000 Hrs

Applications:

- Courtyard
- Private and public garden
- Community
- Causeway

Other Models:

• 40W | 4000LM | GPH-12-40W-MCTP-GY

40W | 4000LM | GPH-12-40W-MCTP-BK











Photometrics: GPH-12-40W-MCTP-BR





BUG Rating: B1-U3-G1

Area 65'x 65' Mounting Height: 9'

Other Views:







Top View

Bottom View

Performance Table: GPH-12-40W-MCTP-BR

| MODEL NO. | Wattage | Voltage | Lumens | Color Temp. | BUG Rating | LPW |
|--------------------|--------------------------|----------|--------------------------------------|-------------------------|------------|-----|
| GPH-12-40W-MCTP-BR | 12W 20W 30W 40W | 120-277V | 1200LM 2000LM 3000LM 4000LM | 3000K 4000K 5000K | B1-U3-G1 | 100 |

Sample Ordering

| Model | del Size | | | Watt Color Temp. | | p. | Housing | |
|-------|----------|----|----|------------------|---|------|---------|----|
| GPH | _ | 12 |]- | 40W | _ | MCTP | _ | BR |

Accessories:

Blank = No Option For Accessories

Blank = No Option For Accessories OPT-GPH-3IN-BR = 3IN POLE ENTRY Bronze

Other Models: GPH-12-40W-MCTP-BK







Top View

Bottom View



