
LDS SERIES OUTDOOR LIGHTING



LDS-MCT5-DT-ORB



Customer Name: Project Name: Note:



Ideal for Hallways, bedrooms, laundry rooms, bathrooms, alleys, Loading docks, doorway, pathway

Features

- Multi CCT (Selectable Switch on the LED Board)
- **Direct Replacement for Fluorescent**
- **Oil-Rubbed Bronze Finish**

Technical Specifications

Electrical:

- Voltage: 120V AC 50/60Hz
- Output Voltage: 36VDC
- Power Factor: >0.90
- Wattage: 15W
- Efficacy: 100 LPW
- Total Harmonic Distortion: ≤15 %

Mechanical:

- **Oil-Rubbed Bronze Finish**
- Housing: Steel base with Die-cast Rings
- High-Transmission Frosted Plastic Lens With Excellent • Distribution and Uniformity
- Maximum Ambient Temperature: 50~113°F
- Rated life: 50,000 Hrs
- Wet Location

- 7-Year Warranty
- Housing: Steel base with Die-cast Rings
- High-Transmission Frosted Plastic Lens With Excellent Distribution and Uniformity

Lighting:

Selection:

- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- Total Lumens: 1500LM
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- Multi CCT (Selectable Switch on the LED Board)
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 120°

Applications:


Hallways, bedrooms, laundry rooms, bathrooms, alleys, Loading docks, doorway, pathway.

Other Models:

15W | 1500LM | LDS-MCT5-DT-SIL







Front View

Back View

Performance Table: LDS-MCT5-DT-ORB

Side View

| MODEL NO. | Wattage | Voltage | Lumens | Color Temp. | BUG Rating | LPW |
|-----------------|---------|---------|--------|-------------------------------|-------------------|-----|
| LDS-MCT5-DT-ORB | 15W | 120V | 1500LM | 2700K/3000K/3500K/4000K/5000K | B0-U3-G1 | 100 |



FACTORY-INSTALLED OPTION:



OPI-EM-LDS EMERGENCY BATTERY BACKUP



OPT-SEN-LDS-BR

PROGRAMMABLE MICROWAVE

BI-LEVEL SENSOR

WEC-8RC OPTIONAL REMOTE CONTROL



OPT-PC-B1 BUTTON

Example:

1. LDS-MCT5-DT-ORB

Blank = No Option For Accessories

OPT-PC-B1 = BUTTON

OPT-EM-LDS = EMERGENCY BATTERY BACKUP

WEC-8RC= OPTIONAL REMOTE CONTROL

OPT-SEN-LDS-BR = PROGRAMMABLE MICROWAVE BI-LEVEL SENSOR

2. LDS-MCT5-DT-ORB

OPT-EM-LDS

(FOR LDS 15W MCT5 FIXTURE 120V) (FOR LDS 15W MCT5 FIXTURE 120V) (EMERGENCY BATTERY BACKUP)

WESTGATE



