

LDSXL SERIES Outdoor Lighting

LDSXL-MCT-DD-BK

24" OUTDOOR/INDOOR LED DECORATIVE WALL SCONCE

MCT Multi Color Temperature (Selectable)



AVAIL FINISHES:




Wall sconce fixture updated with the latest in LED technology. It provides accent illumination that visually expands the space and creates a relaxing atmosphere. Ideal for use in hallways, stairways, dining areas, foyers, and meeting rooms for residential and commercial applications. The long LED life, coupled with exceptional color rendering, make this fixture attractive for new or retrofit projects.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



24 1/6"(H) x 6"(W) x 4"(D)

Features

- High-Transmission Frosted Plastic Lens with Excellent Distribution and Uniformity
- Direct replacement for Fluorescent
- Full distribution LED luminaries
- 70,000 Hours Rated Life
- 7-Year Warranty

Technical Specifications

Electrical:

- Voltage: 120-277V
- Wattage: 25W
- Power factor: >0.9
- Efficacy: 72 LPW

Mechanical:

- Die-cast Aluminum Housing with Powder Coat Finish
- High-Transmission Frosted Plastic Lens with Excellent Distribution and Uniformity
- Direct replacement for Fluorescent
- Full distribution LED luminaries
- IP Rating: IP65
- Operating Temperature: -4°F to 113°F
- Suitable for Wet Locations

Lighting:

- Dimming: (Dual Function) Triac Dimmable at 120V & 0-10V Dimming at 120-277V
- Multi CCT: Selectable CCTs Switch located on the LED Board
- Total Lumens: 1800LM
- Color Temperature: 3000K/ 4000K/ 5000K
- Color Rendering Index: ≥ 80
- Beam Angle: 120°

Applications:

- Motel, Hotels, Hospitals, hallways, stairways, dining areas, foyers, and meeting rooms

Other Models:

- 25W | 1800LM | LDSXL-MCT-DD-SIL
- 25W | 1800LM | LDSXL-MCT-DD-ORB




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com





WG-ZB-ZB-2Z


Photometrics: LDSXL-MCT-DD-BK



BUG Rating: B1-U3-G1



Other Views:



Bottom View



Front View



Side View



Back View

Performance Table: LDSXL-MCT-DD-BK

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LDSXL-MCT-DD-ORB	25W	120V	1800LM	3000K 4000K 5000K	B1-U3-G1	75

Sample Ordering

Model Color Temp. Dimming Housing

LDSXL - MCT - DD - BK

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-LDSXL = EMERGENCY BATTERY BACKUP

OPTION

OPT-EM-LDSXL-277V = EMERGENCY BATTERY BACKUP

OPTION

OPT-PC-B = BUTTON

FACTORY-INSTALLED OPTION:



OPT-EM-LDSXL
OPT-EM-LDSXL-277V
EMERGENCY BATTERY
BACKUP OPTION

