




2" wall mount bracket (ACC-WM2) and 4" square pole adaptor with 2" tendon (PSS45TZ)



Slip fitter adjust 90-degrees above and below center

DIMENSIONS:

12-1/2"(W) x 9-3/4"(H) x 2-1/2"(D) x 12-1/4"(SF)



LF3-100CW-SF LF3-100WW-SF

LED Flood Lights 3 Series with Slip Fitter

Ideal for general site lighting, alleys, loading docks, doorways, pathway, parking areas. Replace existing HID flood lights/wall packs Great for use with motion sensors or other instant on/off controls. Solid state lighting technology for long life, low maintenance and high efficiency.

ELECTRICAL SPECIFICATIONS:

- Voltage: 100-277VAC 50/60Hz
- Wattage: 100W
- Input current: 1.2A Max
- Other wattages: 80W, 100W, 150W, 300W
- Power factor: PF≥0.90
- Output voltage: 36-60VDC
- Output current: 2.5A
- Driver efficiency: 88%

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish (Dark Bronze)
- Operating temperature: -30 —+40 °C
- Lifespan: 50000Hrs.
- IP rating: IP65, Wet Locations
- 100% dip-tested under load
- Main Structure: aluminum + Optical Lens
- Storage temperature humidity: -40 —+80 °C , 10—90% RH

CERTIFICATIONS:



Other Options (Field Installed):

Order future:

LF3-220CW LF3-220WW



Order Mounting:

LF3-SF Slip fitter

LF3-YOK Yoke

Includes strain relief connector

Junction box with knockout

Includes strain relief connector

Example: LF3 (series) - 220 (wattage) - CW (color temp) = LF3-220CW + LF3-EXTARM (mounting)

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LF3-100CW-SF	100W	100~277V AC	11021 LM	5000K
LF3-100WW-SF	100W	100~277V AC	10035 LM	3000K

LIGHTING SPECIFICATIONS:

- Dimmable
- LED type/brand: SMD 3030/ Lumileds LEDs
- Total lumens: 25684lm and 21578lm
- Color temperature: 3000K / 4000K / 5000K / 5700K
- Color rendering index: >80
- Beam angle: 120x90°
- Luminance: 10000Lm (DLC)
- Luminous Efficiency: 99 Lm/W (DLC)
- LED quantity: 120 PCS
- LED efficacy: 120Lm/W

SAFETY & EMC:

- Safety norms: UL1598, UL8750, EN60598, EN61347-2-13, EN62031, EN62471
- Withstand voltage: I/P-FG: 2121VDC
- Grounding resistance: ≤0.5Ω,OK
- Electromagnetic compatibility: EN55015, EN61000-2-3, EN61000-3-3, EN61547
- Gross weight: YK 12.5lbs TR 13.4lbs SF 16.3lbs MA 14lbs
- Quantity / Carton: 1pc

WARRANTY: 7 years



JOB NAME: _____

DATE: _____

TYPE: _____

LF3-100CW-SF LF3-100WW-SF


LED Flood Lights 3 Series with Slip Fitter



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LF3-100CW-SF	100W	100~277V AC	11021 LM	5000K
LF3-100WW-SF	100W	100~277V AC	10035 LM	3000K

PHOTOMETRICS:

Spectral Power Distribution & Chromaticity Diagram




Illuminance Plots


Distance (ft)	Illuminance at a Distance	
	Center Beam fc	Beam Width
17.0ft	11.90 fc	35.3 ft 64.4 ft
34.0ft	2.97 fc	70.7 ft 128.8 ft
51.0ft	1.32 fc	106.0 ft 193.1 ft
68.0ft	0.74 fc	141.4 ft 257.5 ft
85.0ft	0.48 fc	176.7 ft 321.9 ft
102.0ft	0.33 fc	212.1 ft 386.3 ft

■ Vert. Spread: 92.2°
■ Horiz. Spread: 124.3°

Photometric Data



ISOCANDELA DIAGRAM



ISOLUX DIAGRAM

