




DIMENSIONS:

9-7/8"(H) x 12-5/8"(W) x 3-3/8"(D)



LF3-150CW-YK
LF3-150WW-YK

LF3 ARCHITECTURAL SERIES FLOOD LIGHT
WITH YOKE

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LF3-150CW-YK	150W	120~277V AC	18000 LM	5000K
LF3-150WW-YK	150W	120~277V AC	15500 LM	3000K

Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 150W
- Other wattages: 80W,100W
- Power factor: >0.95
- Efficacy: 90LM/W~95LM/W

LIGHTING SPECIFICATIONS:

- LED type/brand: Lumileds / SMD 3030
- Total lumens: 15500LM and 18000LM
- Color temperature: 4000K / 5000K
- Color rendering index: >82
- Beam angle: 90° x 110°

WARRANTY: 7 years

HOUSING SPECIFICATIONS:

- Die cast aluminum
- Outdoor powder coat finish (Dark Bronze)
- Operating temperature: -40°F ~ 104°F
- Lifespan: 50000 Hrs.
- IP rating: IP65, Wet Locations

CERTIFICATIONS: UL, DLC

