


DIMENSIONS:



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP.
LFLV-12W-50K	12W	12VAC/DC	900LM	5000K
LFLV-12W-30K	12W	12VAC/DC	800LM	3000K

ACCESSORIES INCLUDED:



2ft. SPT-2 18AWG Lead Wire 8-1/2" Non-metallic Spike

LIGHTING SPECIFICATIONS:

- Light Source: Nichia 757 UL-Recognized LED Controller and SMD LED Array (Non-Dimmable)
- Lens: Prismatic Reflector + Optic LED Lens and Glass Front Lens
- Total lumens: 900LM/800LM
- Color Temperature: 5000K/3000K
- Beam Angle: 60°

WARRANTY: 1 years



LFLV-12W-50K LFLV-12W-30K

12V INTEGRATED LED LANDSCAPE UPLIGHTS

Ideal for walkway and pathway, stairway and more.

ELECTRICAL SPECIFICATIONS:

• Voltage: 12V AC/DC • Wattage: 12W

Efficacy: 75LM/W/66LM/W

HOUSING SPECIFICATIONS:

- ADC 12 Cast Aluminum with Powder Coat (Bronze Finish)
- 2FT. STP-2 18AWG lead wire
- 8-1/2" Non-metallic Spike
- Silicon-filled Wire Nuts
- IP rating: IP67, Wet Locations

CERTIFICATIONS:







