

# LFX-MD SERIES Outdoor Lighting

LFX-MD-15-50W-30K-TR

LFX-MD-15-50W-40K-TR

LFX-MD-15-50W-50K-TR

**MP** Multi Power/Wattage (Selectable)




**WESTGATE**  
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_

Type: \_\_\_\_\_



Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas.

## Features

- DLC Premium & LED High-Lumen Flood lights
- Solid State Lighting Technology for Long Life
- No Maintenance Needed and High-Efficiency
- 70,000 Hours Rated Life
- 7-Year Warranty
- Optic Lens Type: III
- Multi-Power - The Switch is on the bottom of the Fixture

## Technical Specifications

### Electrical:

- Voltage: 120~277V AC/50~60 Hz
- Wattage: Selectable Wattages (15W/20W/30W/50W)
- Power Factor: >0.9
- Efficacy: 130 LPW

### Mechanical:

- Die-cast Aluminum Housing with Powder Coat Finish (Dark Bronze and White Finish)
- Solid State Lighting technology for long life, no Maintenance needed and High-Efficiency
- High Conductive Aluminum LED Board
- 270° Adjustable Yoke Mount
- IP Rating: IP65
- Operating Temperature: -40°F to 104°F
- Suitable for Wet Locations

### Lighting:

- Dimming: 0~10V Dimmable
- Optic Lens Type: III
- Cord type: 13" #18 AWG stranded wires
- Total Lumens: 6500LM Max.
- Color Temperature: 3000K/4000K/5000K
- Color Rendering Index: ≥ 82
- Beam Angle: 120°X 90°

### Applications:

- Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas.
- Replace existing HID flood lights/ wall packs

## Other Models:



- 30W | 4080LM | LFX-SM-10-30W-30K-TR
- 30W | 4080LM | LFX-SM-10-30W-40K-TR
- 30W | 4080LM | LFX-SM-10-30W-50K-TR




Phone: (877) 805-2252 | Fax: (877) 805-2252  
www.westgatemfg.com |



**Photometrics:** LFX-MD-15-50W-50K-TR



BUG Rating: B3-U0-G1




Area 45'x 55' Mounting Height: 20'


**Other Views:**



Side View



Front View



Back View

**Performance Table:** LFX-MD-15-50W-TR

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LFX-MD-15-50W-30K-TR	15W	120~277V	1950LM	3000K 4000K 5000K	B3-U0-G1	130
LFX-MD-15-50W-40K-TR	20W		2600LM			
	30W		3900LM			
LFX-MD-15-50W-50K-TR	50W		6500LM			



# Sample Ordering

Model	Size	Min.Wattage	Max.Wattage	Color Temp.	Mount
LFX	MD	15	50W		TR

30K = 3000K  
 40K = 4000K  
 50K = 5000K

## Accessories Options

Blank = No Option For Accessories  
 WRC-3-BRZ = Weatherproof cover with three(3) 1/2" hubs  
 LF3-SH2 = Shroud for LF3 50W Reversible  
 LF3-SH2FG = Full-Glare Shroud for LF3 50W

## ACCESSORIES AND MOUNTING OPTIONS



LF3-SH2  
Shroud (Reversible)



LF3-SH2FG  
Full-Glare Shroud

## Color Options: Custom Color Available

Black Silver White Dark Bronze Green Red Yellow  
Default color



## Example:

1. LFX-MD-15-50W-50K-TR
2. LFX-MD-15-50W-50K-TR  
WRC-3-BRZ

(For LFX 15-50W 5000K fixture 120V-277V)

(For LFX 15-50W 5000K fixture 120V-277V)  
 (Weatherproof cover with three(3) 1/2" hubs)

