



LFX-XXL SERIES Outdoor Lighting

LFX-XXL-300-600W-50K
POWER-ADJUSTABLE FLOOD/AREA LIGHT


WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!



Customer Name: _____

Project Name: _____

Note: _____ Type: _____



25 5/8"(H) x 12-3/4"(W) x 3-3/8"(D)

Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas.

Features

- Housing: ADC12 Aluminum heat sink, outdoor powder coating
- Optical Lens: High light transmittance PC, anti-UV and flame resistant
- 70,000 Hours Rated Life
- 7-Year Warranty
- Multi-Power - The Switch is On the Bottom of the Fixture

Technical Specifications

Electrical:

- Voltage: 100-277V AC, 50/60Hz
- Wattage: 300W/ 400W/ 500W/ 600W
- Power Factor: >0.9
- THD<20%
- Efficacy: 140 LPW

Mechanical:

- With Snap-on & Bolt Mounting Options for One- Person Installations. Select a Mounting Option (Sold Separately)
- LED: LUMILEDS 2835 /5050 LED
- Housing: ADC12 Aluminum heat sink, outdoor powder coating
- NEMA Twist-Lock Shorting Cap Included. Photocell Sold Separately
- 10KV Lightning Surge Protection
- Aluminum LED board: High conductive, waterproof, aging resistance, salt mist resistance, ensure the safety and long life span
- Operating Temperature: -104°F to 122°F
- Effective projected areas (EPA's) are:
 - Front = 0.38 square feet
 - Side = 0.30 square feet
 - Face = 1.05 square feet
- IP Rating: IP65
- Suitable for Wet Locations

Lighting:

- Dimming: 0~10V dimmable
- Optical Lens: High light transmittance PC, anti-UV and flame resistant
- Lens: TYPE III°
- Total Lumens: 84000LM Max.
- Color Temperature: 3000K/ 4000K/ 5000K
- Color Rendering Index: ≥ 82
- Beam Angle: 120°X 90°

Applications:

- Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas.
- Replace existing HID flood lights/ wall packs





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com | www.westgatecontrols.com




WG-ZB-Y6-2Z

Photometrics: LFX-XXL-300-600W-50K



600W 5000K BUG Rating: B5-U5-G5



600W 5000K Area 65'x 115' Mounting Height: 20'

Other Views:



Side View



Bottom View



Front View



Back View

Performance Table: LFX-XXL-300-600W-50K

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LFX-XXL-300-600W-50K	300W 400W 500W 600W	120~277V	42000 56000 70000 84000	5000K	B5-U5-G5	140

Sample Ordering

Model Size Min.Wattage Max.Wattage Color Temp.

LFX - XXL - 300 - 600W -
50K = 5000K

Accessories Options

Blank = No Option for Accessories
WEC-8RC = Remote Control for OPT-SEN-3MR-4

Factory Installed Options

Blank = No Factory Installed Options
OPT-010W/PO = 0-10V Dim. Wires Pulled Out
OPT-CLR-95 = Color Paint
OPT-CIR_MC = 260 Set up fee per project
OPT-LF3-PCK = Twist Lock Photocell
OPT-3MPC = Microwave Photocell with a 1/2" threaded

SENSOR AND REMOTE CONTROL OPTIONS



WEC-8RC Remote control




OPT-SEN-3MR-3 Bi-Level Motion Sensor



EPA Rating:

Model						
LFX-XXL	1.1	1.7	2.1	2.3	2.06	2.9

Mounting Options:




Color Options: LFX-XXL-300-600W-50K
 Custom Color Available



Black Silver White **Dark Bronze** Green Red Yellow
Default color




Shroud & Wire Guard: LFX-XXL-300-600W-50K



LF-SHROUD-F
 Shroud
 12 5/8" x 10 5/8" x 5 1/2"



LF-SHROUD-G
 Full-Glare Shroud
 12 3/4" x 10 5/8" x 5 1/2"



COLOR CHART: * Choose from one of our Premium Colors with no set-up fee.

Gloss:



SILVER METALLIC
70 GLOSS
T357-GR105



SILVER METALLIC
30 GLOSS
T353-GR06



DARK RED 90
GLOSS
P009-RD02



INTERNATIONAL
ORANGE 90
GLOSS
T009-OG26



SAFETY ORANGE
90 GLOSS
T009-OG01



YELLOW 90
GLOSS
T009-YL14



YELLOW 90
GLOSS
T009-YL01



TRAFFIC GREEN
70 GLOSS
T007-GN16



GREEN 70 GLOSS
T007-GN13



GREEN 60 GLOSS
C006-GN03



BLUE 90 GLOSS
T009-BL01



DARK BLUE 80
GLOSS
T008-BL20



RAL 8028 TERRA
BROWN 90 GLOSS
C209-BR358

Hammer:




WHITE HAMMER
T013-WH09



BEIGE HAMMER
T013-BG38



GREY HAMMER
C013-GR08



SILVER
HAMMERTONE
T064-GR05




BLACK HAMMER
T013-BK62




RED HAMMER
T013-RD15



GREEN HAMMER
T013-GN220



BLUE HAMMER
T013-BL468



BRONZE HAMMER
T012-BR161

Texture:



WHITE TEXTURE
C031-WH120



FLINT GRAY
TEXTURE
T243-GR522



BLACK TEXTURE
C241-BK109



RED TEXTURE
T241-RD129



BLUE TEXTURE
C241-BL544




OIL RUBBED
BRONZE TEXTURE
T291-BR251


Vein:



BLACK/WHITE
VEIN
T075-WH34



SILVER VEIN
T375-BK26



COPPER VEIN
EXTERIOR
T075-BK211



GOLD VEIN
T375-BK10



COPPER VEIN
T375-BK07

