

JOB NAME: _____

DATE: _____

TYPE: _____

DIMENSIONS:

24"(L) x 6-7/8"(W) x 2-6/8"(H)



LLHB3-2FT-100W-40K
LLHB3-2FT-100W-50K

LED LINEAR HIGH BAYS

Ideal for one-for-one replacement of conventional lighting systems such as HID and fluorescent. Applications include manufacturing, warehousing and other large indoor spaces with mounting heights from 10 ft. to 40 ft. Luminaire shall be suspended at a minimum 24 inches from the ceiling.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120~277 VAC/50~60 Hz
- Wattage: 100 W
- Power factor: >0.95
- Efficacy: 145LM/W

HOUSING SPECIFICATIONS:

- Extruded Aluminum housing
- Aluminum heat sink
- Operating temperature: -40 °F ~ 122 °F

CERTIFICATIONS: UL, DLC



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LLHB3-2FT-100W-40K	100W	100~277V AC	14500 LM	4000K
LLHB3-2FT-100W-50K	100W	100~277V AC	14500 LM	5000K



3.5 FT. Adjustable Suspension Kit
 With Ceiling Mount Disks (Included)



Surface Mounting Kit
 (Included)

LIGHTING SPECIFICATIONS:

- Dimming: 0~10V dimmable
- Lens: Optical lens
- Total lumens: 14500 LM
- Color temperature: 4000K & 5000K
- Color rendering index: >80

WARRANTY: 7 years

