

LLHB4 SERIES

Industrial Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

LLHB4-300W-MP-40K-D-480V

LLHB4-300W-MP-50K-D-480V

MULTI POWER 4TH GENERATION OF LINEAR HIGH BAYS




Customer Name: _____

Project Name: _____

Note: _____

Type: _____



46 3/4" (L) X 17 3/4" (W) X 2" (H)

Ideal for replacement of conventional lighting systems such as HID and fluorescent. Applications include manufacturing warehousing and other large indoor spaces with mounting heights from 10ft. to 40ft. the fixture can be surface mounted also.

Features

- High Quality LED Chips To Provide High Efficiency, Heat Dissipation
- Stability, And Lumen Maintenance.
- Polycarbonate Lens, High Flame Retardant Point
- 50,000 Hours Rated Life
- 5-Year Warranty

Technical Specifications

Electrical:

- Voltage: 480V
- Wattage: 150W/225W/300W
- Power Factor: >0.95
- Efficacy: 136 LPW

Mechanical:

- Surge Protector
- Steel Housing
- Steel Thickness: 24 Gauge
- V-Hooks
- Unprecedented Quality.
- Aluminum LED Board
- Operating Temperature: -4°F ~ 131°F
- Suitable for Damp Locations

Lighting:

- Dimming: 0~10V Dimmable
- Lens: Polycarbonate Lens
- Total lumens: 40800LM (Per Industry Standards, Lumens are Reported Without Frosted Lens)
- Color Temperatures: 4000K and 5000K
- Color Rendering Index: >80
- Wide Beam Angle

Applications:

- Warehouse
- Manufacturing Plants Distribution Centers
- Industrial Commercial
- Grocery Stores Gymnasiums
- Cold Storage

Other Models:



- 200W | 27200LM | LLHB4-200W-MP-40K-D-480V
- 200W | 27200LM | LLHB4-200W-MP-50K-D-480V




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |



Photometrics: LLHB4-300W-MP-D-480V



BUG Rating: B5-U3-G4



Other Views:



Front View



Side View



Back View

Performance Table: LLHB4-300W-MP-D-480V

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LLHB4-300W-40K-D-480V	150W	120~277V	27200LM	4000K	B5-U3-G4	136
	225W		34000LM			
LLHB4-300W-50K-D-480V	300W		40800LM	5000K		

Sample Ordering

Model Wattage Multi PowerColor Temp. Dimming Volt

LLHB4 - 300W - MP - [] - D - 480V

40K = 4000K
50K = 5000K


Accessory Options

SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 10FT. 1/16" SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS
SCL-GSY20 = HEAVY-DUTY ADJUSTABLE 20FT. 1/16" SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS
LLHB4-RODKIT = OPTIONAL ROD KIT, 3-1/4" DIA. X 40" H
WEC-2MD-35 = SENSOR COMPONENT


Factory-Installed Options

Blank = No Option
OPT-SEN-LLHB4 = MICROWAVE BI-Level SENSOR
OPT-EM-HB4INT = INTERNAL EMERGENCY BATTERY BACKUP
OPT-LLHB4-SMK = SURFACE MOUNTING OPTION
OPT-FWH-63 = 6FT 3-WIRE WHIP
OPT-FWH-65 = 6FT 5-WIRE WHIP
OPT-FWH-66 = 6FT 6-WIRE WHIP
OPT-HBC-125TL-WH = 8FT, 15A, 125V, WHITE
OPT-HBC-277TL-WH = 8FT, 15A, 277V, WHITE
OPT-HBC-125SB-WH = 10FT, 15A, 125V, 18/3STR, WHT

OPTIONAL ACCESSORIES



SCL-GSY10
SCL-GSY20



LLHB4-RODKIT
(Fixture Shown with LLHB4-RODKIT)



LLHB4-SMK
(Fixture Shown with LLHB4-SMK)



WEC-2MD-35
(Fixture Shown with WEC-2MD-35)

EMERGENCY BATTERY BACKUP AND SENSOR OPTIONS



OPT-EM-HB4INT



OPT-SEN-LLHB4

