
LMIR SERIES Indoor Lighting

LMIR-MC18-2432-MCT-DF








LED Mirrors And Cabinet Dimming With Defogger Feature Ideal for office, Retail Store, Showroom, Residential applications and Damp environment lighting applications.

Customer Name:

Project Name:



32"(H) x 24"(W) x 5"(H)

eatures

- Frontlit (Bar Pattern)
- Touch Sensor Switch
- Finish: Aluminium Frame

- 5mm Copper Free Silver Mirror
- MCT: Brightness & CCT Touch Buttons Located on The Mirror

Technical Specifications

Electrical:

Voltage: 120V AC 60Hz

Wattage: 35W Power Factor: >0.95

Total Harmonic Distortion: ≤ 20 %

Lighting:

- Multi-CCT: Brightness & CCT Touch Buttons Located on The Mirror
- Color Temperatures: 2700K ~ 6500K Color Rendering Index: CRI ≥ 90
- 50.000 Hours Rated Life

Mechanical:

- Finish: Aluminium Frame
- Frontlit (Bar Pattern)
- Touch Sensor Switch
- Demister Pad
- IP44, Indoor Use only
- Operating Temperature: -22°F to 104°F
- 5-Year Warranty

Applications:

LED Mirrors And Cabinet Dimming With Defogger Feature Ideal for Office, Retail Store, Showroom, Residential Applications and Damp Environment **Lighting Applications**

Other Models:

• 39W | LMIR-36-2436-MCT-DF









Other Views:







Side View Bottom View Mounted View

Performance Table: LMIR-MC18-2432-MCT-DF

MODEL NO.	Wattage	Voltage	Color Temp.
			2700K
LMIR-MC18-2432-MCT-DF	35W	120V	~
			6500K

Sample Ordering

Model Size Dimension Color Temp. Function

LMIR - MC18 - 2432 - MCT - DF

Other Model: LMIR-18-2028-MCT-DF







Side View Front View Mounted View