

# LOHB SERIES OUTDOOR LIGHTING

LOHB-2FT-50W-30K  
LOHB-2FT-50W-50K


Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_ Type: \_\_\_\_\_



Selection:



22 3/4"(L) x 3"(H) x 4 1/2"(W)

This outdoor lighting is Ideal for Wall wash, sign, suspended outdoor/indoor lighting, small stadium and tracks

## Features

- Die-cast Aluminum with Black Powder Coat Finish
- Removable 1/2" NPT Threaded Knuckles Included
- 7-Year Warranty
- Removable Half Shroud Included

## Technical Specifications

### Electrical:

- Voltage: 120~277V; 50/60Hz AC
- THD: <20%
- Power Factor: >0.9
- Wattage: 50W
- Efficacy: 130 LPW

### Mechanical:

- Die-cast Aluminum with Black Powder Coat Finish
- Removable 1/2" NPT Threaded Knuckles Included
- Cord Type: 3.2 SJTW 18/3 AWG cable
- Removable Half Shroud Included
- Operating Temp: -40°F to 104°F
- Rated life: 50,000 hrs
- Wet Location
- IP Rating: IP65

### Lighting:

- LED: Philips Lumileds Luxeon 3030 High Flux LED
- Total Lumens: 6700LM/6500LM
- Color Temperatures: 3000K/5000K
- Color Rendering Index: CRI ≥ 70
- Beam Angle: 90°

### Applications:



- Ideal for Wall wash, sign, suspended outdoor/indoor lighting, small stadium and tracks

### Other Models:


- 120W | 15000LM | LOHB-4FT-120W-30K
- 120W | 15000LM | LOHB-4FT-120W-50K



## Photometrics: LOHB-2FT



BUG Rating: B3-U0-G0



Billboard Size: 5'x 17.5' Mounting Distance: 6'

## Other Views:



Side View



Front View



Back View

## Performance Table: LOHB-2FT

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LOHB-2FT-50W-30K	50W	120-277V	6500LM	3000K	B3-U0-G0	130
LOHB-2FT-50W-50K	50W	120-277V	6700LM	5000K	B3-U0-G0	134

## Sample Ordering

**Model**      **Size**      **Watt**      **Color Temp.**  
 -  -  -

30K = 3000K  
 50K = 5000K

## Accessories:

Blank = No Option For Accessories  
 LOHB-C= Surface/Ceiling mounting conversion Bracket (set of 2)  
 LOHB-H-2FT= 2Ft. Mounting Bracket, Hot-Rolled Steel

## Example:

- LOHB-2FT-50W-30K (FOR LOHB 50W 3000K OUTDOOR LIGHT FIXTURE 120-277V)
- LOHB-2FT-50W-30K LOHB-C (FOR LOHB 50W 3000K OUTDOOR LIGHT FIXTURE 120-277V) (FOR SURFACE/CEILING MOUNTING CONVERSION BRACKET)

## ACCESSORIES:



**LOHB-C**  
 Surface/Ceiling mounting conversion Bracket, (set of 2)



**LOHB-H-2FT**  
 2Ft. Mounting Bracket, Hot-Rolled Steel  
 (The picture shows 2-fixture installation  
 Can be used with one fixture too)