



LRD SERIES RESIDENTIAL LIGHTING

LRD-10W-27K-3WTRSL
LRD-10W-30K-3WTRSL
LRD-10W-35K-3WTRSL
LRD-10W-40K-3WTRSL
LRD-10W-50K-3WTRSL

3" LED ARCHITECTURAL WINGED SLOT RECESSED LIGHTS



Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



Ideal for New as well as old residential and commercial constructions.

Features

- 3" (2-1/8" Actual) LED Slot Recessed Trim
- Die-Cast Aluminum With White Powder Coat Finish
- 5-Year Warranty
- Junction Box Included With Fixture

Technical Specifications

Electrical:

- Voltage: 120VAC
- Wattage: 10W
- Power factor: >0.90
- Efficacy: Up to 70 LM/W

Mechanical:

- Up to 9 AWG18 Wires
- Die-Cast Aluminum With White Powder Coat Finish
- Clear Glass Lens
- Junction Box Rated Up to 9 AWG18 Wires
- Type IC Rated: Approved for Direct Contact With Insulation
- Operating Temperature: 104°F
- Air-Tight and Type IC Rated: No Housing Required
- Damp Location Approved
- 5-Year Warranty

Lighting:

- Dimming: Dimmable down to 10% using standard TRIAC LED dimmer
- Total Lumens: 700LM
- Color Temperature: 2700K/3000K/3500K/4000K/5000K
- Color Rendering Index: >90
- Beam Angle: 10°
- Lifespan: 50,000 Hrs.

Applications:



- Ideal for New as well as old residential and commercial constructions.

Other Models:


- 7W | 490LM | LRD-10W-27K-3WTRSL-WH/BK
- 7W | 490LM | LRD-10W-30K-3WTRSL-WH/BK
- 7W | 490LM | LRD-10W-35K-3WTRSL-WH/BK
- 7W | 490LM | LRD-10W-40K-3WTRSL-WH/BK
- 7W | 490LM | LRD-10W-50K-3WTRSL-WH/BK



Photometrics: LRD-10W-3WTRSL



BUG Rating: B1-U2-G0



Other Views:



LRD-WTR3SL-WH
 LRD-WTR3SL-WH
 LRD-WTR3SL-WH
 LRD-WTR3SL-WH
 LRD-WTR3SL-WH

LRD-EGN-10W-27K-D
 LRD-EGN-10W-30K-D
 LRD-EGN-10W-35K-D
 LRD-EGN-10W-40K-D
 LRD-EGN-10W-50K-D

LRD-10W-27K-3WTRSL-WH
 LRD-10W-30K-3WTRSL-WH
 LRD-10W-35K-3WTRSL-WH
 LRD-10W-40K-3WTRSL-WH
 LRD-10W-50K-3WTRSL-WH



LRD-WTR3SL-BK
 LRD-WTR3SL-BK
 LRD-WTR3SL-BK
 LRD-WTR3SL-BK
 LRD-WTR3SL-BK

LRD-EGN-10W-27K-D
 LRD-EGN-10W-30K-D
 LRD-EGN-10W-35K-D
 LRD-EGN-10W-40K-D
 LRD-EGN-10W-50K-D

LRD-10W-27K-3WTRSL-BK
 LRD-10W-30K-3WTRSL-BK
 LRD-10W-35K-3WTRSL-BK
 LRD-10W-40K-3WTRSL-BK
 LRD-10W-50K-3WTRSL-BK

Performance Table: LRD-7W-3WTRSL

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LRD-10W-27K-3WTRSL	10W	120V	700LM	2700K	B1-U2-G0	70
LRD-10W-30K-3WTRSL				3000K		
LRD-10W-35K-3WTRSL				3500K		
LRD-10W-40K-3WTRSL				4000K		
LRD-10W-50K-3WTRSL				5000K		



Accessory:

Blank = No Option For Accessories
LRD-FGL = LRD SERIES FROSTED GUASS LENS

Accessory:



LRD-FGL

Sample Ordering

Model	Wattage	Color Temp.	Size	Size
LRD	10W	<input type="text"/>	3WTRSL	<input type="text"/>
		27K = 2700K 30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K		WH = WHITE BK = BLACK

