

JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

**DIMENSIONS:**

10-5/8"(L) x 10-5/8"(W) x 4-3/4"(D)



**LRS-C-30K-D**  
**LRS-C-40K-D**

**LED DIMMABLE RESIDENTIAL LIGHTS**

Ideal for general site lighting, residential houses, doorway, pathway and garages

**ELECTRICAL SPECIFICATIONS:**

- Voltage: 120ACV
- Wattage: 12W
- Power Factor: 0.95
- Efficacy: 91LM/W

**HOUSING SPECIFICATIONS:**

- Aluminum housing with powder coated
- Operating temperature: -40°F to 104°F
- Lifespan: 50,000 hr.
- IP Rating: IP65

**CERTIFICATIONS:ETL**



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LRS-C-30K-D	12W	120ACV	1100LM	3000K
LRS-C-40K-D	12W	120ACV	1100LM	4000K

**LIGHTING SPECIFICATIONS:**

- Dimmable: Dimmable with standard LED dimmers (TRIAC)
- LED: DOB
- Total lumens: 1100LM
- Color temperature: 3000K/4000k
- Color rendering index: >80

**WARRANTY: 7 years**

