LSL SERIES

Commercial Lighting



Multi Color Temperature (Selectable)



LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.

Ideal choice for residential, commercial, and industrial lighting. Steady performance and long lifetime. Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below

Features

- High Lumen Efficiency
- Ceiling Mount or Suspended Mount
- The Sensor Can Be Overridden (Disconnected)

Technical Specifications

Electrical:

- Voltage: 120-277VAC 60Hz
- Wattage: 40W
- Power Factor: >0.99
- Efficacy: 105 LPW

Mechanical:

Whit Finish


- Bi-Level Microwave Motion Sensor Inside the Fixture Under The Lens.
- Lens: Polycarbonate Frosted Lens, Shatter Resistant
- Translucent Lens Caps Illuminate With The Light.
- Integrated Lens & LED Module for Easy Installation & Maintenance.
- Ceiling Mount or Suspended Mount
- Junction Box Cover Kit Included, It Sits on Any 3" or 4" Round Junction Boxes
- Operating Temperature: -4°F -122°F
- Housing: Cold-rolled Steel
- Lens: Polycarbonate Frosted Lens
- IP44 Suitable For Damp Location
- 5-Year Warranty


Sensor Spec:


- Detection Range: 17Ft. / 360°
- Mounting Height: 25Ft. Max.
- DIP Settings switch on The Sensor
- Optional Remote Control (WEC-3RC)

Other Models:

• 20W | 2100LM | LSL-2FT-20W-MCT-D-EM-SEN







- Linkable (Optional Alignment Bracket Available)
- MCT: Multi Color Temperature (Selectable Switch Inside Fixture)

Emergency Battery Backup Spec:

- Output Power: 9W
- Output Voltage: 48V
- Li-Ion Battery: >90 Minutes Emergency Operation
- Test Button Installed on The Side of The Fixture

Lighting:

- MCT: Multi Color Temperature (Selectable Switch Inside Fixture)
- Dimmable: 0~10V Dimming
- Total Lumens: 4200LM
- Color Temperatures: 3500K/ 4000K/ 5000K
- Color Rendering Index: CRI ≥ 80
- Reduces Energy Consumption Up to 80% Compared to a Fluorescent Fixture

Applications:

- LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.
- Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below
- Ideal for residential, commercial, and industrial lighting. Steady performance and long lifetime

80W | 8400LM | LSL-8FT-80W-MCT-D-EM-SEN







WESTGATE THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Photometrics: LSL-4FT-40W-MCT-D-EM-SEN 45 40 Luminaire Lumens Uplight 35 30 25 20 15 2fc 1fc 10 0.5fc 5 0.1fc Front 0 15 25 35 50 55 5 10 20 30 40 45 BUD Rating: B1-U3-G2 40W 5000K, Area 45'x 55' Mounting Height: 9'

Other Views:

	2	
Front View	Side View	Back View

Performance Table: LSL-4FT-40W-MCT-D-EM-SEN

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LSL-4FT-40W-MCT-D-EM-SEN	40W	120~277V	4200LM	3500K 4000K 5000K	B2-U4-G2	105
Sample Ordering	ACCESSORIES:					
Model Size Wattage						
LSL = 4FT = 40W =						
Accessories:				SCL-GSY110 SCL-GS	SY120 SCL-TBC	-WN
Blank = No Option For Accessories LSL-CB = LSL SERIES ALIGNMENT BRACKET SCL-TBC-WN = T-BAR CLIP WITH SUSPENSION HOLE SCL-CSY = ADJUSTABLE 1/16" 6FT. SUSPENSION KIT T-BAR CLIPS + 1 CABLE BUSHING + 3 PLASTIC TIE ST SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT. S LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT. S LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SCL-GSY110 = ADJ. 20FT 1/16in SINGLE SUSPENSION GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8 SCL-GSY120 = ADJ. 20FT 1/16in SINGLE SUSPENSION GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8 LSL-4FT-WG = WIRE GUARD KIT FOR 4FT. STRIP LIGH LSL-4FT-WK = SHOP LIGHT WING KIT Factory-Installed Options	WITH Y-CONNECTO RAPS - 70 LBS. MA SUSPENSION KIT W : SET) USPENSION KIT W : SET) CABLE WITH Y HO 3FT.) CABLE WITH Y HO 3FT.) T	R KEY HOLE SET + 2 X LOAD ITH Y-CONNECTOR & ITH Y-CONNECTOR & OK ENDS. LOOP		ALIGNMENT (COUPL BRACKET	ING) SCL-CS SCL-GSY20	Y
Blank = No Option For Accessories OPT-HBC-125TL-WH = NEMA TWIST-LOCK PLUG 8FT, OPT-HBC-277TL-WH = NEMA TWIST-LOCK PLUG 8FT, OPT-HBC-125SB-WH = STRAIGHT BLADE PLUG 10FT,	15A, 277V	CTOR 18AWG		LSL-4FT-WG	LSL4FT-I	

WESTGATE

OPT-HBC-125SB-WH OPT-HBC-125TL-WH OPT-HBC-277TL-WH

