

LSL-8FT-80W-40K-D-A
LSL-8FT-80W-50K-D-A

Customer Name: _____

Project Name: _____


Note: _____ Type: _____



Selection:



LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc. Engineered with stable performance LED engines and the world's top brand LED driver. Same footprint as traditional 2-lamp strip lights.



96"(L) x 4 1/2"(W) x 3 3/4"(H)

Features

- LED Strip Lights
- Strip Line Cover
- White Finish
- Split Version, Req. 5min Assembly
- 50,000 Hours Rated Life
- 5-Year Warranty
- Lens: Frosted Diffuse Polycarbonate Lens with Strip Lines Inside

Technical Specifications

Electrical:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 80W
- Power Factor: >0.98
- Efficacy: 105 LPW

Mechanical:

- White Finish
- Housing: Heavy Die-Formed Steel, White Powder Coated
- Lens Snaps into the tabs of the Housing Fixture
- Ceiling-Mounted
- Same Footprint as Traditional 2-lamp Strip Lights
- Mounting: Surface Mount, Wall Mount or Suspended
- IP44 Suitable For Damp Location
- Operating Temperature: -22°F -104°F

Lighting:



- Dimmable: 0~10V Dimming
- Chip: Samsung
- Total Lumens: 8400LM
- Color Temperatures: 4000K/ 5000K
- Color Rendering Index: CRI ≥ 80
- IP Rating: IP44

Applications:


- Ideal for architectural lighting solutions
- A variety of industrial, commercial and residential applications




Photometrics: LSL-8FT-D-A



BUD Rating: B3-U4-G3



Other Views:



Front View



Side View



Back View

Performance Table: LSL-8FT-D-A

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LSL-8FT-80W-40K-D-A	80W	120~277V	8400LM	4000K	B3-U4-G3	105
LSL-8FT-80W-50K-D-A	80W	120~277V	8400LM	5000K	B3-U4-G3	105

Sample Ordering

Model	Size	Wattage	Color Temp.	Feature	Version
LSL	8FT	80W		D	A

40K = 4000K
50K = 5000K

Accessories:

Blank = No Option For Accessories

LSL-4FT-WK = SHOP LIGHT WING KIT (2 SETS FOR 8FT)

SCL-GSY110 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT (3 PER FIXTURE)

SCL-GSY120 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT (3 PER FIXTURE)

LSL-CB = ALIGNMENT BRACKET

Factory-Installed Options:

Blank = No Option For Accessories

OPT-EM-CM1INT= INTERNAL EMERGENCY BACKUP BATTERY

OPT-SEN-2US= ULTRASONIC BI-LEVEL DIMMING

OPT-SEN-2USRC = OPTIONAL RC

OPT-SEN-LLHB-OC1 = LLHB-OC1 EXTERNAL STANDARD PIR OPT-SENSOR

OPT-HBC-125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V, WHITE

OPT-HBC-277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V, WHITE

OPT-HBC-125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A,125V, 3-CONDUCTOR 18AWG,WHITE

OPT-SEN-DAYLIGHT = DAYLIGHT HARVESTING SENSOR WORKS WITH ABOVE OPT-SEN-2US

Example:

- LSL-8FT-80W-40K-D-A (For LSL 80W 4000K FIXTURE 120-277V)
- LSL-8FT-80W-40K-D-A (For LSL 80W 4000K FIXTURE 120-277V)
LSL-4FT-WK (SHOP LIGHT WING KIT)
- LSL-8FT-80W-40K-D-A (For LSL 80W 4000K FIXTURE 120-277V)
LSL-4FT-WK (SHOP LIGHT WING KIT)
OPT-SEN-2US (ULTRASONIC BI-LEVEL DIMMING REMOTE NOT NEEDED)

ACCESSORIES:



LSL-4FT-WK
(2 SETS)



SCL-GSY110



SCL-GSY120



LSL-CB

FACTORY-INSTALLED OPTIONS:



OPT-HBC-125SB-WH



OPT-HBC-125TL-WH



OPT-HBC-277TL-WH



OPT-EM-CM1INT



OPT-SEN-2US



OPT-SEN-LLHB-OC1



OPT-SEN-2USRC



OPT-SEN-DAYLIGHT

