

LSL SERIES

Commercial Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

LSL-8FT-80W-MCT-D



MULTI-CCT
MCT Selection:


LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc. Engineered with stable performance LED engines and the world's top brand LED driver. Same footprint as traditional 2-lamp strip lights.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



96"(L) x 4 1/2"(W) x 3 3/4"(H)

Features

- LED Strip Lights
- Strip Line Cover
- 5-Year Warranty
- 50,000 Hours Rated Life
- Lens: Frosted Diffuse Polycarbonate Lens with Strip Lines Inside
- MCT: Multi Color Temperature (Selectable Switch Inside Fixture)

Technical Specifications

Electrical:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 80W
- Power Factor: >0.98
- Efficacy: 105/ 108/ 107 LPW

Mechanical:

- White Finish
- Housing: Heavy Die-Formed Steel, White Powder Coated
- Lens Snaps into the tabs of the Housing Fixture
- Ceiling-Mounted
- Same Footprint as Traditional 2-lamp Strip Lights
- Mounting: Surface Mount, Wall Mount or Suspended
- IP44 Suitable For Damp Location
- Operating Temperature: -22°F -104°F

Lighting:

- Dimmable: 0~10V Dimming
- Chip: Samsung
- Total Lumens: 8420LM/ 8560LM/ 8700LM
- Color Temperatures: 3500K/ 4000K/ 5000K
- Multi-CCT (selectable switch inside fixture)
- Color Rendering Index: CRI ≥ 80
- IP Rating: IP44

Applications:

- Ideal for architectural lighting solutions, a variety of industrial, commercial and residential applications

Other Models:

- 20W | 2270LM | LSL-3FT-30W-MCT-D
- 30W | 3280LM | LSL-3FT-30W-MCT-D
- 40W | 4350LM | LSL-4FT-40W-MCT-D
- 60W | 6560LM | LSL-6FT-60W-MCT-D
- 84W | 13200LM | LSL-8FT-84W-MCT-D-HL





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-Z5-2C-2Z

Photometrics: LSL-8FT-MCT




BUD Rating: B3-U4-G3



Other Views:



Front View



Side View



Back View

Performance Table: LSL-8FT-MCT

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LSL-8FT-80W-MCT-D	80W	120~277V	8420LM	3500K	B3-U4-G3	105
			8560LM	4000K		107
			8700LM	5000K		108

Sample Ordering

Model Size Wattage Color Temp. Feature

LSL - 8FT - 80W - MCT - D

Accessories:

Blank = No Option For Accessories

LSL-4FT-WK = SHOP LIGHT WING KIT (2 SETS FOR 8FT)

SCL-GSY110 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT (3 PER FIXTURE)

SCL-GSY120 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT (3 PER FIXTURE)

LSL-CB = ALIGNMENT BRACKET

Factory-Installed Options:

Blank = No Option For Accessories

OPT-EM-CM1INT= INTERNAL EMERGENCY BACKUP BATTERY

OPT-SEN-2US= ULTRASONIC BI-LEVEL DIMMING

OPT-SEN-2USRC = OPTIONAL RC

OPT-SEN-LLHB-OC1 = LLHB-OC1 EXTERNAL STANDARD PIR OPT-SENSOR

OPT-HBC-125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V, WHITE

OPT-HBC-277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V, WHITE

OPT-HBC-125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A, 125V, 3-CONDUCTOR 18AWG, WHITE

OPT-SEN-DAYLIGHT = DAYLIGHT HARVESTING SENSOR WORKS WITH ABOVE OPT-SEN-2US

Example:

- LSL-8FT-80W-MCT-D (FOR LSL 80W MCT FIXTURE 120-277V)
- LSL-8FT-80W-MCT-D (FOR LSL 80W MCT FIXTURE 120-277V)
LSL-4FT-WK (SHOP LIGHT WING KIT)
- LSL-8FT-80W-MCT-D (FOR LSL 80W MCT FIXTURE 120-277V)
LSL-4FT-WK (SHOP LIGHT WING KIT)
OPT-SEN-2US (ULTRASONIC BI-LEVEL DIMMING REMOTE NOT NEEDED)

ACCESSORIES:



LSL-4FT-WK
(2 SETS)



SCL-GSY110



SCL-GSY120



LSL-CB

FACTORY-INSTALLED OPTIONS:



OPT-HBC-125SB-WH



OPT-HBC-125TL-WH



OPT-HBC-277TL-WH



OPT-EM-CM1INT



OPT-SEN-2US



OPT-SEN-LLHB-OC1



OPT-SEN-2USRC



OPT-SEN-DAYLIGHT

