LSN SERIES Commercial Lighting

LSN-8FT-64W-40K-D LSN-8FT-64W-50K-D

8FT NARROW STRIP




Customer Name: Proiect Name: Note: Type:



Selection:

LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.

Ideal choice for residential, commercial, and industrial lighting. Steady performance and long lifetime. Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below



96"(L) x 3"(W) x 3 1/4"(H)

eatures

- High Lumen Efficiency
- Ceiling Mount or Suspended Mount

Linkable (Optional Alignment Bracket Available)

Technical Specifications

Electrical:

Voltage: 120-277VAC 60Hz

Wattage: 64W

Power Factor: >0.99

Efficacy: 130 LPW

Mechanical:

- Whit Finish
- Lens: Polycarbonate Frosted Lens, Shatter ResistantTranslucent Lens Caps Illuminate With The Light.
- Integrated Lens & LED Module for Easy Installation & Ceiling Mount or Suspended Mount
- Junction Box Cover Kit Included, It Sits on Any 3" or 4" **Round Junction Boxes**
- Operating Temperature: -4°F -122°F
- Housing: Cold-rolled Steel
- Lens: Polycarbonate Frosted Lens
- IP20, Indoor Use Only
- 5-Year Warranty

Lighting:

Dimmable: 0~10V Dimming

Total Lumens: 8320LM

Color Temperatures: 4000K/5000K

Color Rendering Index: CRI ≥ 80

Reduces Energy Consumption Up to 80% Compared to a Fluorescent Fixture

Rated life: 50,000 Hrs

Applications:

- LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.
- Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options
- Ideal for residential, commercial, and industrial lighting. Steady performance and long lifetime

Other Models:

- 40W | 5200LM | LSN-4FT-40W-35K-D 40W | 5200LM | LSN-4FT-40W-40K-D
- 40W 5200LM | LSN-4FT-40W-50K-D











Photometrics: LSN-8FT-64W-D





Other Views:







Performance Table: LSN-8FT-64W-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LSN-8FT-64W-40K-D LSN-8FT-64W-50K-D	64W	120~277V	8320LM	3500K 4000K 5000K	B2-U4-G3	130

Sample Ordering

Model Size Wattage Color Temp.

LSN 8FT 64W D 40K = 4000K

50K = 5000K

Accessories:

Blank = No Option For Accessories

LSN-CB = LSN SERIES ALIGNMENT BRACKET

SCL-TBC-WN = T-BAR CLIP WITH SUSPENSION HOLE ON TOP. WING NUT AND WASHER INCL. SCL-CSY = ADJUSTABLE 1/16" 6FT. SUSPENSION KIT WITH Y-CONNECTOR KEY HOLE SET + 2 T-BAR CLIPS + 1 CABLE BUSHING + 3 PLASTIC TIE STRAPS - 70 LBS. MAX LOAD

SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY20 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY110 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

SCL-GSY120 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

LSN-4FT-WG = WIRE GUARD KIT FOR 4FT OR SET OF 2 FOR 8FT LSN STRIP LIGHT

Factory-Installed Options:

Blank = No Option For Accessories

OPT-EM-CM1INT= INTERNAL EMERGENCY BACKUP BATTERY

OPT-SEN-2MDR-36= PROGRAMMABLE MICROWAVE BI-LEVEL

OPT-HBC-125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V

OPT-HBC-277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V

OPT-HBC-125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A,125V, 3-CONDUCTOR 18AWG

WEC-3RC = OPTIONAL REMOTE

ACCESSORIES:





LSN-4FT-WG

FACTORY-INSTALLED OPTIONS:







OPT-HBC-125SB-WH

OPT-HBC-125TL-WH

OPT-HBC-277TL-WH







OPT-EM-CM1INT

OPT-SEN-2MDR-36

