


LSS SERIES Commercial Lighting





Multi Color Temperature & Multi Power/Wattage (Selectable)





LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.

Ideal choice for residential, commercial, and industrial lighting. Steady performance and long lifetime. Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below

88 3/4"(L) x 2 3/5"(W) x 2 2/3"(H)

Features

- High Lumen Efficiency
- Ceiling Mount or Suspended Mount

- Linkable (Optional Alignment Bracket Available)
- MCT: Multi Color Temperature (Selectable 4Power Switch Inside Fixture)

Technical Specifications

Electrical:

Voltage: 120-277VAC 60HzWattage: 55W/ 65W/ 75W/ 90W

Power Factor: >0.99Efficacy: 135 LPW

Mechanical:

- Black Finish
- High Lumen Efficiency Lumen
- Lens: Polycarbonate Frosted Lens, Shatter Resistant
- Ceiling Mount or Suspended Mount
- Operating Temperature: -4°F to 122°F
- Housing: Cold-rolled Steel
- IP44, Suitable For Damp Location
- 5-Year Warranty

Lighting:

- Dimmable: 0~10V DimmingTotal Lumens: 11745LM Max.
- Color Temperatures: 3500K/ 4000K/ 5000K
- Multi-CCT (Selectable 4Power switch inside fixture)
- Color Rendering Index: CRI ≥ 80
- Reduces Energy Consumption Up to 80% Compared to a Fluorescent Fixture
- Rated life: 50.000 Hrs

Applications:

- LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.
- Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below
- Ideal for residential, commercial, and industrial lighting. Steady performance and long lifetime

Other Models:

• 90W | 11745LM | LSS-8FT-90W-MCTP













Photometrics: LSS-8FT-90W-MCTP-BK





Other Views:

Side View Front View Back View

Performance Table: LSS-8FT-90W-MCTP-BK

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LSS-8FT-90W-MCTP-BK	55W 65W 75W 90W	120~277V	7425LM 8775LM 10125LM 11745LM	3500K 4000K 5000K	B3-U4-G3	135

Sample Ordering

Model		Size		Wattage	Color Temp	. Housing
	LSS	8FT	_	90W	MCTP	■ BK

Accessories:

Blank = No Option For Accessories

LSS-CB2 = ALIGNMENT BRACKET

SCL-TBC-WN = T-BAR CLIP WITH SUSPENSION HOLE ON TOP. WING NUT AND WASHER INCL. SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY20 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY110 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

SCL-GSY120 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

SCL-CSY1-6FT= ADJ. 6FT 1/16 in SINGLE SUSPENSION 5 in CANOPY SET WITH Y DOUBLE KEYHOLE END CONNECTORS, NONPOWER SIDE

SCL-CSY1P-6FT = ADJ. 6FT 1/16in SINGLE SUSPENSION 5in CANOPY SET WITH Y DOUBLE KEYHOLE END CONNECTORS, POWER SIDE WITH SJTW18/5 WHITE CORD

Factory-Installed Options:

Blank = No Option For Accessories

OPT-EM-CM2INT= INTERNAL EMERGENCY BACKUP BATTERY

OPT-SEN-2US = ULTRASONIC BI-LEVEL DIMMING (REMOTE NOT NEEDED)

OPT-HBC-125TL-BK = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V

OPT-HBC-277TL-BK = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V

OPT-HBC-125SB-BK = STRAIGHT BLADE PLUG 10FT, 15A,125V, 3-CONDUCTOR 18AWG

WEC-3RC = OPTIONAL REMOTE OPT-FWH-63 = 6FT 3-WIRE WHIP

OPT-FWH-63 = 6FT 5-WIRE WHIP

ACCESSORIES:

SCL-GSY10



SCL-CSY1-6FT SCL-CSY1P-6FT

FACTORY-INSTALLED OPTIONS:

SCL-GSY20







