LVC SERIES Indoor Lighting


LVF-36-MCT5-BN
36" MULTI-CCT VANITY LIGHTS

MUIti Color Temperature (Selectable)



This is LED Vanity Model Ideal for office, Retail Store, Showroom, Residential applications and Damp environment lighting applications.





Features

- Corrosion and Heat Resistance Powder Coated
- Finish: Brushed Nickel
- Durable Die-cast Aluminum

- Lens Type: Polycarbonate Lens
- MCT: Multi Color Temperature (Selectable Switch Inside Fixture)

Technical Specifications

Electrical:

Voltage: 120V AC 50/60Hz

Wattage: 24WPower Factor: >0.95

Total Harmonic Distortion: ≤ 20 %

Efficacy: 83 LPW

Mechanical:

- Corrosion and Heat Resistance Powder Coated
- Finish: Brushed Nickel
- Durable Die-cast Aluminum
- Lens Type: Polycarbonate Lens
- IP20, Suitable for Damp Location
- Operating Temperature: -22°F to 104°F

Lighting:

- Dimming: TRIAC Dimming (Dimmable Down to 5% Compatible with Traic and ELV Dimmers)
- Total Lumens: 2000LM
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- Multi-CCT(Selectable Switch Inside Fixture)
- Color Rendering Index: CRI ≥ 90
- 50,000 Hours Rated Life
- 5-Year Warranty
- Beam Angle: 104.8°(H) x 100.5°(V)

Applications:

 Ideal for Office, Retail Store, Showroom, Residential Applications and Damp Environment Lighting Applications

Other Models:

 $\bullet 12W \mid 1020 LM \mid LVF-18-MCT5-BN \bullet 16W \mid 1360 LM \mid LVF-24-MCT5-BN \bullet 24W \mid 2000 LM \mid LVF-36-MCT5-BN \bullet 32W \mid 2700 LM \mid LVF-48-MCT5-BN \bullet 12W \mid 1020 LM \mid LVF-18-MCT5-BN \bullet 12W \mid 1020 LM \mid 10$













Photometrics: LVF-36-MCT5-BN Lusinaire Lumenz Uplight John Japan Bud Rating: B1-U3-G1 Area 55'x 55' Mounting Height: 9'

Other Views:



Performance Table: LVF-36-MCT5-BN

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LVF-36-MCT5-BN	24W	120V	2000LM	2700K 3000K 3500K 4000K 5000K	B1-U3-G1	83

Sample Ordering

Model	Size	Color Temp. Housing
LVF -	36	– MCT5 – BN

Other Model: LVF-24-MCT5-BN

