

LVTE SERIES Industrial Lighting

LVTE-4FT-30-46W-MCTP

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)




Customer Name: _____

Project Name: _____

Note: _____

Type: _____



46 2/3"(W) x 4 1/6"(H) x 3 1/4"(D)

Suitable for restaurants, bakeries, food facilities, gyms, pool areas workshops, garages, canopies, parking garages, cold storage facilities, food processing facilities, farmyards, and other harsh, humid, dusty, and wet environment lighting applications, and any application where NSF certified fixtures or high-end architectural designer grade fixtures are required.

NSF/ANSI 2:2015 Food Equipment: Splash Zone: Equipment surfaces that are subject to splash and food spillage during operation of the equipment other than those in a direct contact food-zone.

Features

- LED Linear Vapor Light
- Grey Finish
- 5-Year Warranty
- 50,000 Hours Rated Life
- Lens: Opal Polycarbonate
- Vandal-Proof Polycarbonate Lens
- MCT: Multi Color Temperature & Power (Selectable Switch Inside Fixture)

Technical Specifications

Electrical:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 30W/38W/46W
- Power Factor: >0.9
- Efficacy: 140LM/W

Mechanical:

- Grey Finish
- Housing: Polycarbonate
- Vandal-Proof Polycarbonate Lens
- 1/2" NPT knockout on both ends. Liquid Tight Cord Connectors Incl.
- Polycarbonate Construction Highly Impacts Resistant
- UV-Stabilized Polycarbonate Diffuser Eliminates Glare
- Diffuser Crystals Enhance Even Light Distribution
- Stainless Steel Clips Evenly Seal The Luminaire
- Stainless Steel Clamp
- Operating Temp:-25.6°F to 104°F
- Suitable For Wet Locations
- IP Rating: IP66

Lighting:

- Dimmable: 0~10V Dimming
- LED SMD Type: 2835
- Total Lumens: 6400LM Max.
- Multi-CCT & Power(Selectable Switch Inside Fixture)
- Color Temperatures: 3500K/4000K/5000K
- Color Rendering Index: CRI ≥ 80

Applications:



- Ideal for offices, retail stores, showrooms, and residential applications. Uniquely suited for areas where accessing the fixture is challenging
- Suitable for restaurants, bakeries, food facilities, gyms, pool areas, and any application where NSF certified fixtures or high-end architectural designer grade fixtures are required.
- NSF/ANSI 2:2015 Food Equipment: Splash Zone: Equipment surfaces that are subject to splash and food spillage during operation of the equipment other than those in a direct contact food-zone

Other Models:


- 35W | 4900LM | LVTE-4FT-20-35W-MCTP
- 60W | 8400LM | LVTE-4FT-30-60W-MCTP



Photometrics: LVTE-4FT-30-46W-MCTP



BUG Rating: B2-U3-G2



Area 45'x 55' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: LVTE-4FT-30-46W-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LVTE-4FT-30-46W-MCTP	30W	120~277V	4200LM	3500K	B2-U3-G2	140
	38W		5320LM	4000K		
	46W		5400LM	5000K		

Sample Ordering

Model	Size	Wattage	Color Temp.
LVTE	4FT	30	46W - MCTP

Factory-Installed Options:

Blank = No Option For Accessories
 OPT-EM-CM1INT= INTERNAL EMERGENCY BACKUP BATTERY
 OPT-HBC-125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V, WHITE
 OPT-HBC-277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V, WHITE
 OPT-HBC-125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A,125V, 3-CONDUCTOR 18AWG,WHITE
 OPT-SEN-2MDR-36=PROGRAMMABLE MICROWAVE BI-LEVEL SENSOR
 WEC-3RC=OPTIONAL REMOTE CONTROL

SENSOR AND EMERGENCY BATTERY BACK UP OPTIONS:



OPT-HBC-125SB-WH



OPT-HBC-125TL-WH



OPT-HBC-277TL-WH



OPT-EM-CM1INT



OPT-SEN-2MDR-36



WEC-3RC

