

**EXCLUSIVE
PATENT-PENDING
TECHNOLOGY**



zinc
die-cast

This time-saving product makes the job easier. The bending of bare wire is no longer necessarily since the lug may be rotated in 3 different positions.

FEATURES:

- :: No more loop
- :: Wire range: #14 through #4
- :: Available in 2 sizes of 1/2" and 3/4"
- :: Meets NEC (National Electric Code) requirements.

Ref: **UL** File#: **E317815**

FEED-THROUGH ARMORED GROUND CLAMP

ITEM NO.	TRADE SIZE	WIRE SIZE	STD. PKG.	
			INNER	MASTER
MVP94-50	1/2"	#14-4	-	125
MVP94-75	3/4"	#14-4	20	80



zinc
die-cast

FEATURES:

- :: Trade size: available from 1/2" to 4"
- :: Insulated bushing with ground lug
- :: Combination screw head (Phillips, flat blade and pan head) 1", insulated ground bushing, threaded type with set screw, bushing
- :: Material: Malleable Iron, Lug Material: Aluminum.
- :: Wire size: 14 AWG (solid) - 4 AWG (stranded). For copper or aluminum wire.

APPLICATION:

- :: Used with locknut to terminate rigid or IMC conduit to box

Ref: **UL** File#: **E207816**

GROUND BUSHINGS INSULATED & LAY-IN LUG

ITEM NO.	TRADE SIZE	STD. PKG.	
		INNER	MASTER
GBILA-1	1/2"	50	500
GBILA-2	3/4"	40	400
GBILA-3	1"	25	250
GBILA-4	1-1/4"	25	250
GBILA-5	1-1/2"	25	250
GBILA-6	2"	10	100
GBILA-7	2-1/2"	5	50
GBILA-8	3"	5	50
GBILA-9	3-1/2"	4	40
GBILA-10	4"	4	40



C19

Rigid-IMC Conduit

