


JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_



D: 4.875" (123.8mm) H: Height: 1.875" (47.6mm)

## RDL4-ADJ-27K RDL4-ADJ-30K RDL4-ADJ-41K RDL4-ADJ-50K

### 4" LED Adjustable Baffle Trim

Isolated driver for improved thermal management.

#### ELECTRICAL SPECIFICATIONS:

- Voltage: 120V AC
- Wattage: 10W
- Power factor: 90% +

#### LIGHTING SPECIFICATIONS:

- LED type/brand: EPISTAR chip (COB)
- Driver-36,000-hour design life
- Dimmable: Yes
- Lumen: 650 lm
- Color temperature: 2700K, 3000K (Warm white), 4100K(Natural white) and 5000K (Daylight)
- CRI: 90

#### OTHERS:

- Net weight: 0.76lbs / 345g

#### WARRANTY:

- Five-year warranty

MODEL NO	WATTS	LUMENS	VOLTAGE	COLOR TEMP
RDL4-ADJ-27K	10W	650LM	120V AC	2700K
RDL4-ADJ-30K	10W	650LM	120V AC	3000K
RDL4-ADJ-41K	10W	650LM	120V AC	4100K
RDL4-ADJ-50K	10W	650LM	120V AC	5000K

#### HOUSING SPECIFICATIONS:

- Housing: Spun aluminum with white powder coat finish
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Wet locations: Suitable for damp locations
- Maximum ambient 4 °C (104 °F)

#### CERTIFICATIONS:

- UL listed
- Energy Star-rated (2700K, 3000K, and 4100K)
- Pending Energy Star rating for 5000K version

