



RSL SERIES RESIDENTIAL LIGHTING

RSL4-G2-MCT5-ORB
RSL G2 SECOND GENERATION SLIM WAFER LIGHTS
MCT5 Multi Color Temperature (Selectable)

Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



LED DOWNLIGHTS (SMOOTH TRIM) - 4" ROUND Ideal for New As Well As Old Residential And Commercial Constructions.

Features

- 4" Smooth Recessed Trim
- Multi CCT (Selectable Switch on the Back of the driver)
- Isolated Driver for Improved Thermal Management
- 5-Year Warranty
- Spun Aluminum with White Powder Coat Finish

Technical Specifications

Electrical:

- Voltage: 120V AC
- Output Voltage: 36VDC
- Power Factor: >0.90
- Wattage: 10W
- Efficacy: 70 LPW
- Total Harmonic Distortion: ≤15 %

Mechanical:

- 1/4" Thick
- Up to 9 AWG18 Wires
- Die-Cast Aluminum With Powder Coat Finish
- Pot Light Housing Is Not Required Even For Insulated Ceiling
- Junction Box 1" Thick Included With Fixture
- Typel Crated: Approved For Direct Contact With Insulation
- Maximum Ambient Temperature: -40°F to 104°F
- Damp Location

Lighting:

- Dimming: Dimmable Down to 10% Using a Standard TRIAC LED Dimmer
- Lens: 0.125" White Translucent Acrylic
- Can Rotate after Installation to Align
- LED: Seoul DOB (Driver On Board) Technology
- Optics: White Translucent Acrylic
- Total Lumens: 700LM
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- Multi CCT (Selectable Switch on the Back of the driver)
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 100°-110°
- Rated life: 50,000 hrs

Applications:


- LED recessed trims have been designed to be a flexible lighting solution for new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:


- 12W | 1000LM | RSL6-G2-MCT5-ORB



Photometrics: RSL4-G2-MCT5-ORB



BUG Rating: B2-U1-G0




9W 5000K, Area 30'x 30' Mounting Height: 9'

Other Views:



Side View



Front View



Junction box 1-1/4" thick included with fixtures

Back View

Performance Table: RSL4-G2-MCT5-ORB

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
RSL4-G2-MCT5-ORB	10W	120V	700LM	2700K 3000K 3500K 4000K 5000K	B2-U1-G0	70

Sample Ordering

Model Generation Color Temp. Finish

RSL4 - G2 - MCT5 - ORB

Accessories:

Blank = No Option For Accessories

RSL-EXT-10FT-MCT = 10 FT. EXTENSION CABLE FOR USE WITH ALL SLIM LIGHT

RSL4-RI-13 = 4" ROUND ROUGH-IN PLATE, 13" LONG

RSL4-RI = 4" ROUND ROUGH-IN PLATE, 26" LONG

RSL-346-RIBH = 3", 4", 6" (ADJUSTABLE) ROUND GALVANIZED PLATE WITH BAR HANGERS

E26-CONVERTER = SCREW-IN ADAPTER THAT FITS ANY STANDARD

RSL4-GR = GOOF RING FOR 4IN LIGHTS WITH BUTTERFLY WINGS

RSL4-TRM-BK = 4" Black Clip-on Trim

RSL4-TRM-ORB = 4" Oil-rubbed Bronze Clip-on Trim

RSL4-TRM-CU = 4" Copper Clip-on Trim

RSL4-TRM-BZ = 4" Bronze Clip-on Trim

RSL4-TRM-BN = 4" Brushed Nickel Clip-on Trim

RSL4-TRM-CH = 4" Chrome Clip-on Trim

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-DL1EXT = EXTERNAL BATTERY BACKUP

ACCESSORIES:



E26-CONVERTER
Includes Medium Base E-26
Screw-in Adapter That Fits Any
Standard



RSL4-RI-13
4" Round Rough-in Plate,
13" Long



RSL-EXT-10FT-MCT
10 Ft. Extension Cable for use
with all Slim Light



RSL-346-RIBH
3", 4", 6" (Adjustable) Round Galvanized
plate with Bar Hangers



RSL4-RI
4" Round Rough-in Plate,
26" Long




Clip-on Trims
BK ORB CU BZ BN CH

FACTORY-INSTALLED OPTION:



OPT-EM-DL1EXT
EXTERNAL BATTERY BACKUP



RSL4-GR
Goof Ring For 4in Lights With Butterfly
Wings



Compatible Dimmer List:

MODEL NO.	BRAND
6631-1LT	LEVITON
MACL-153MLH-AL	LUTRON
TGCL-153PH-LA	LUTRON
DVW-603PGH-WH	LUTRON
CT-600PR-WH	LUTRON
LGCL-153PHL-IV	LUTRON
TGCL-153PH-LA	LUTRON
LSLV603PWV	LUTRON
6674-POW	LEVITON
DVCL-153P	LUTRON
MSCL-OP153P	LUTRON
CTCL-153P	LUTRON
MACL-153M	LUTRON
HCL453PTCCCV6	PASS & SEYMOUR
LSLV603PWV	PASS & SEYMOUR

