

JOB NAME: _____

DATE: _____

TYPE: _____



Junction box 1" thick included with fixtures

- RSL6-ADJ-27K
- RSL6-ADJ-30K
- RSL6-ADJ-40K
- RSL6-ADJ-50K

LED ADJUSTABLE ULTRA SLIM RECESSED LIGHTS

Ideal for New as well as old residential and commercial constructions.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120VAC
- Wattage: 12W
- Power factor: >0.90
- Efficacy: Up to 75LM/W

HOUSING SPECIFICATIONS:


- Die-cast Aluminum with white powder coat finish
- Pot light housing is not required even for insulated ceiling
- Junction box 1" thick included with fixture
- Type IC rated: Approved for direct contact with insulation
- Operating temperature: -40°F ~ 104°F
- Lifespan: 50,000 Hrs.
- Air-tight and damp location approved

CERTIFICATIONS: ETL,ES



DIMENSIONS:

Depth: 0.75"



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
RSL6-ADJ-27K	12W	120VAC	900LM	2700K
RSL6-ADJ-30K	12W	120VAC	900LM	3000K
RSL6-ADJ-40K	12W	120VAC	900LM	4000K
RSL6-ADJ-50K	12W	120VAC	900LM	5000K

LIGHTING SPECIFICATIONS:

- Dimming: dimmable
- Lens: 0.125" white translucent acrylic
- Optics: White translucent acrylic
- LED: Seoul DOB (Driver On Board) Technology
- Total lumens: 900LM
- Color temperature: 2700K/3000K/4000K/5000K
- Color rendering index: >80
- Beam Angle: 100° -110°

WARRANTY: 5 years



JOB NAME: _____

DATE: _____

RSL6-ADJ-27K
RSL6-ADJ-30K
RSL6-ADJ-40K
RSL6-ADJ-50K

LED ADJUSTABLE ULTRA SLIM RECESSED LIGHTS

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
RSL6-ADJ-27K	12W	120VAC	900LM	2700K
RSL6-ADJ-30K	12W	120VAC	900LM	3000K
RSL6-ADJ-40K	12W	120VAC	900LM	4000K
RSL6-ADJ-50K	12W	120VAC	900LM	5000K

BRAND OF DIMMERS:

NO.	BRAND	MODEL
1	Leviton	6631-1LT
2	Lutron	MACL-153MLH-AL
3	Lutron	TGCL-153PH-LA
4	Lutron	DVW-603PGH-WH
5	Lutron	CT-600PR-WH
6	Lutron	LGCL-153PHL-IV
7	Lutron	TGCL-153PH-LA
8	Lutron	LSLV603PWV
9	Leviton	6674-POW
10	Lutron	DVCL-153P
11	Lutron	MSCL-OP153P
12	Lutron	CTCL-153P
13	Lutron	MACL-153M
14	Pass & Seymour	HCL453PTCCCV6
15	Pass & Seymour	LSLV603PWV

