

RSL SERIES RESIDENTIAL LIGHTING

RSL6-MCT5

LED ULTRA SLIM RECESSED LIGHTS


WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



6 6/7" x 6 2/3"

LED DOWNLIGHTS (SMOOTH TRIM) - 6" ROUND Ideal for New As Well As Old Residential And Commercial Constructions.

Features

- 6" Smooth Recessed Trim
- Multi CCT (Selectable Switch on the Back of the driver)
- Isolated Driver for Improved Thermal Management
- 5-Year Warranty
- Spun Aluminum with White Powder Coat Finish

Technical Specification

Electrical:

- Voltage: 120V AC
- Output Voltage: 36VDC
- Power Factor: >0.90
- Wattage: 15W
- Efficacy: 75 LP
- Total Harmonic Distortion: ≤15 %

Mechanical:

- 1/4" Thick
- Up to 9 AWG18 Wires
- Die-cast Aluminum with white powder coat finish
- Pot Light Housing is Not Required Even for Insulated Ceiling
- Junction box 1-1/4" Thick Included with Fixture
- 1/2" KO on both side of the junction box
- Typel Crated: Approved for direct contact with insulation
- Maximum Ambient Temperature: -40°F to 104°F
- Damp Location
- 5-Year Warranty

Lighting:

- Dimming: Dimmable Down to 10% Using a Standard TRIAC LED Dimmer
- Lens: 0.125" White Translucent Acrylic
- Can Rotate after Installation to Align
- LED: Seoul DOB (Driver On Board) Technology
- Optics: White Translucent Acrylic
- Total Lumens: 1125LM
- Color Temperatures: 2700K/ 3000K/ 3500K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on the Back of the driver)
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 100°-110°
- Rated life: 50,000 hrs

Applications:

- LED recessed trims have been designed to be a flexible lighting solution for new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:

- 15W | 1125LM | RDL6-MCT5-ORB




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-Z8-2F-2Z

Photometrics: RSL6-MCT5



BUG Rating: B1-U2-G1



15W 5000K, Area 35'x 35' Mounting Height: 9'


Other Views:



Side View



Front View



Junction box 1-1/4" thick included with fixtures

Back View

Performance Table: RSL6-MCT5

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
RSL6-MCT5	15W	120V	1125LM	2700K	B1-U2-G1	75
				3000K		
				3500K		
				4000K		
				5000K		

Sample Ordering

Model Color Temp.

RSL6 - MCT5

Accessories:

Blank = No Option For Accessories

RSL-EXT-10FT-MCT = 10 FT. EXTENSION CABLE FOR USE WITH ALL SLIM LIGHT

RSL6-RI-13 = 6" ROUND ROUGH-IN PLATE, 13" LONG

RSL6-RI = 6" ROUND ROUGH-IN PLATE, 26" LONG

RSL-346-RIBH = 3", 4", 6" (ADJUSTABLE) ROUND GALVANIZED PLATE WITH BAR HANGERS

RSL6-GR = GOOF RING FOR 6IN LIGHTS WITH BUTTERFLY WINGS

RSL6-TRM-BK = 6" Black Clip-on Trim

RSL6-TRM-ORB = 6" Oil-rubbed Bronze Clip-on Trim

RSL6-TRM-CU = 6" Copper Clip-on Trim

RSL6-TRM-BZ = 6" Bronze Clip-on Trim

RSL6TRM-BN = 6" Brushed Nickel Clip-on Trim

RSL6-TRM-CH = 6" Chrome Clip-on Trim

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-DL1EXT = EXTERNAL BATTERY BACKUP

ACCESSORIES:



E-26

Includes Medium Base E-26 Screw-in Adapter That Fits Any Standard



RSL6-RI-13

6" Round Rough-in Plate, 13" Long



RSL-EXT-10FT-MCT

10 Ft. Extension Cable For use with all Slim Light



RSL-346-RIBH

3", 4", 6" (Adjustable) Round Galvanized plate with Bar Hangers



RSL6-RI

6" Round Rough-in Plate, 26" Long



Clip-on Trims

BK ORB CU BZ BN CH

FACTORY-INSTALLED OPTION:




OPT-EM-DL1EXT

EXTERNAL BATTERY BACKUP



RSL6-GR

Goof Ring For 6in Lights With Butterfly Wings



Example:

1. RSL6-MCT5

(FOR RSL6 15W MCT5 FIXTURE 120V)

2. RSL6-MCT5

(FOR RSL6 15W MCT5 FIXTURE 120V)

OPT-EM-DL1EXT

(EXTERNAL BATTERY BACKUP)



Compatible Dimmer List:

MODEL NO.	BRAND
6631-1LT	LEVITON
MACL-153MLH-AL	LUTRON
TGCL-153PH-LA	LUTRON
DVW-603PGH-WH	LUTRON
CT-600PR-WH	LUTRON
LGCL-153PHL-IV	LUTRON
TGCL-153PH-LA	LUTRON
LSLV603PWV	LUTRON
6674-POW	LEVITON
DVCL-153P	LUTRON
MSCL-OP153P	LUTRON
CTCL-153P	LUTRON
MACL-153M	LUTRON
HCL453PTCCCV6	PASS & SEYMOUR
LSLV603PWV	PASS & SEYMOUR

