RSL SERIES RESIDENTIAL LIGHTING



RSLC6-BF-MCT5

Multi Color Temperature (Selectable)




Customer Name:

Project Name:

Note:

Type:



This is a 6" LED Commercial Slim Recessed Regressed Baffle Lights which are Ideal for New as Well as Old Residential and Commercial Constructions.

Features

- Optics: White Translucent Acrylic
- Die-Cast Aluminum With Powder Coat Finish
- MCT5: Multi Color Temperature (Selectable)
- Junction Box Included With Fixture
- 7-Year Warranty

Technical Specifications

Electrical:

Voltage: 120-277VWattage: 12WPower Factor: >0.9Efficacy: 79 LPW

Mechanical:

- Die-Cast Aluminum With White Powder Coat Finish
- Junction Box Included With Fixture
- Junction Box thickness: 1-3/8"
- Cut-out Hole Diameter: 6-1/4"
- 24" DC cord from driver box to fixture
- Operating Temperature: -4°F to 104°F
- Recessed Mounting
- 5-Year Warranty
- Suitable for Wet location

Lighting:

- MCT5: Multi Color Temperature (Selectable)
- Dimming: 0-10V Dimmable
- Optics: White Translucent Acrylic
- Total Lumens: 900LM
 - Color Temperatures:
 - 2700K/3000K/3500K/4000K/5000K
- Color Rendering Index: CRI ≥ 90
- Rated life: 50,000 Hrs
- Beam Angle: 110°

Applications:

- New as well as Old Residential
- Commercial Constructions

Other Models:

• 24W | 1900LM | RSLC8-BF-MCT5


















Photometrics: RSLC6-BF-MCT5





30 25 20 15 10 2fc 1fc 0.5fc 0.1fc 15 30 35

BUG Rating: B1-U1-G0

Area 35'x 35' Mounting Height: 9'

Other Views:







Side View

Front View

Back View

Performance Table: RSLC6-BF-MCT5

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
RSLC6-BF-MCT5	12W	120~277V	900LM	2700K 3000K 3500K 4000K 5000K	B1-U1-G0	75

Sample Ordering

Model

Baffle Color Temp.

RSLC6 -

BF

MCT5

Accessories:

Blank = No Option For Accessories

RSL6-RI = 6" Round Rough-in Plate, 26" Long RSL6-RI-13 = 6" Round Rough-in Plate, 13" Long

RSL-346-RIBH = 3", 4", 6" (Adjustable) Galvanized plate with Bar Hangers

RSL6-GR = Goof Ring For 6in Lights with Butterf y Wings

ACCESSORIES:




RSL6-RI





RSL6-RI-13 13 1/4" x 9"





RSL-346-RIBH



