


SCSSL SERIES

SCSSL-UD-AP-4FT-MCTP

SCSSL-UD-AP-4FT-MCTP-BK

ARCHITECTURAL 0.4" SLIM UP&DOWN /W SEPARATE CONTROLS LINEAR LIGHT

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)



Avail Finish:



A modern decorative Euro-design suspended light suitable for conference tables, creative offices and department stores.

Features

- LED Superior Architectural Lights
- Aperture Optics Lens
- Aluminum Housing With Sandy White and Black Finish
- MCTP: Multi Color Temperature and Power (Selectable, the switches are inside the Canopy)
- 5-Year Warranty

Technical Specifications

Electrical:

- Voltage: 120-277V AC 50/60Hz
- Wattage: 10W/15W/20W
- Power Factor: >0.9
- LPW: 70LM/W
- Total Harmonic Distortion: ≤19 %

Mechanical:

- Aluminum Housing With Sandy Black and White Finish
- Two 10FT Adjustable Suspension Cables with Canopies Included
- Lens: Aperture Optics Lens
- Operating Temperature: -22°F to +104°F
- IP Rating: IP20, Suitable for damp location
- 5-Year Warranty

Lighting:

- Dimming: (Dual Function) Triac Dimmable at 120V & 0-10V Dimming at 120-277V
- Total Lumens: 1400LM Max.
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- MCTP: Multi Color Temperature and Power (Selectable, the switches are inside the Canopy)
- Color Rendering Index: CRI ≥ 80
- 50,000 Hours Rated Life
- Beam Angle: 120°

Applications:

- Ideal for offices, hotels, corridors, saloons, libraries, meeting rooms, conference halls, and the best solution for modern lighting solutions
- It can be used in any indoor applications

WESTGATE


THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



Canopy Dimension: 44.21"(W) x 1.38"(H) x 4.33"(D)

Fixture Dimension: 44.45"(W) x 2.79"(H) x 7.87"(D)




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-04102022

Photometrics: SCSSL-UD-AP-4FT-MCTP

BUG rating



Iso-illuminance plot



Performance Table: SCSSL-UD-AP-4FT-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
SCSSL-UD-AP-4FT-MCTP	10W	120~277V	700	2700K	B1-U4-G1	70
SCSSL-UD-AP-4FT-MCTP-BK	15W		1050	3000K		
	20W		1400	3500K		
				4000K		
				5000K		

Sample Ordering

Model	Direction	Lens	Size	Color Temp.	Finish					
SCSSL	-	UD	-	AP	-	4FT	-	MCTP	-	
BK = Black WH = White										


Accessories:

Blank = No Option For Accessories
 SCSSL-REC = SCSSL Rounded End Cap
 SCSSL-REC-BK = SCSSL Rounded End Cap. Black
 SCSSL-CEC = SCSSL Coupling End Cap
 SCSSL-CEC-BK = SCSSL Coupling End Cap

Factory-Installed Options:

Blank = No Option For Accessories
 OPT-EM-SCSSL-WH = Factory-Installed EM option, Installed in Deeper Canopy, White
 OPT-EM-SCSSL-BK = Factory-Installed EM option, Installed in Deeper Canopy, Black

ACCESSORIES:



FACTORY-INSTALLED OPTIONS:

