



SCX-6FT-60W-30K-D
SCX-6FT-60W-35K-D
SCX-6FT-60W-40K-D
SCX-6FT-60W-50K-D

LED DIRECT (DOWN) LINEAR LIGHT

Linear Lighting can be customized to your desired length, look & color temperature and can either be suspended, surface, mounted or recessed to suit your needs. Ideal for Storage rooms, Offices Conference rooms, Retail Reception areas, Hallways Education facilities, hotel, restaurants.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120~277VAC/50~60 Hz
- Wattage: 60W
- Power factor: >0.95
- Efficacy: 115LM/W

HOUSING SPECIFICATIONS:


- Low profile design
- aluminum housing with matte white finish
- Surge protector
- Diffuser is snapped into housing
- Shallow depth provides sleek for low-profile appearance
- Driver (Class II/P driver) disconnect provided where required to comply with US codes.
- Make different connection via T/L/X joints on both ends .
- Mounting options: surface, suspended, wall, recessed
- Operating temperature: -13°F ~ 104°F
- IP Rating: IP20

CERTIFICATIONS: UL, DLC



DIMENSIONS:

72"(L) x 2-6/8"(W) x 3-3/8"(H)



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
SCX-6FT-60W-30K-D	60W	120~277VAC	6720LM	3000K
SCX-6FT-60W-35K-D	60W	120~277VAC	6900LM	3500K
SCX-6FT-60W-40K-D	60W	120~277VAC	7080LM	4000K
SCX-6FT-60W-50K-D	60W	120~277VAC	7260LM	5000K

LIGHTING SPECIFICATIONS:

- Dimming: 0~10 Dimmable
- Lens: Opal Polycarbonate Lens
- Total lumens: 6720LM/6900LM/7080LM/7260LM
- Color temperature: 3000K/3500K/4000K /5000K
- Color rendering index: >80
- Wide Beam angle

WARRANTY: 5 years




JOB NAME: _____


DATE: _____

TYPE: _____


OPTIONAL CORNER FIXTURE MODULES:




SCX-L-30K
SCX-L-35K
SCX-L-40K
SCX-L-50K




SCX-T-30K
SCX-T-35K
SCX-T-40K
SCX-T-50K



SCX-X-30K
SCX-X-35K
SCX-X-40K
SCX-X-50K



SCX-IC-30K
SCX-IC-35K
SCX-IC-40K
SCX-IC-50K



MODEL	JOINT TYPE	LUMENS	COLOR TEMP	DIMENSION
SCX-L-30K	L	508LM	3000K	4.92" X 4.92" X 3.35" X 2.75"
SCX-L-35K	L	575LM	3500K	4.92" X 4.92" X 3.35" X 2.75"
SCX-L-40K	L	616LM	4000K	4.92" X 4.92" X 3.35" X 2.75"
SCX-L-50K	L	660LM	5000K	4.92" X 4.92" X 3.35" X 2.75"
SCX-T-30K	T	629LM	3000K	7" X 3.35" X 2.75" X 2.15" X 2.15"
SCX-T-35K	T	726LM	3500K	7" X 3.35" X 2.75" X 2.15" X 2.15"
SCX-T-40K	T	787LM	4000K	7" X 3.35" X 2.75" X 2.15" X 2.15"
SCX-T-50K	T	854LM	5000K	7" X 3.35" X 2.75" X 2.15" X 2.15"
SCX-X-30K	X	733LM	3000K	3.35" X 2.75" X 2.15" X 2.15"
SCX-X-35K	X	863LM	3500K	3.35" X 2.75" X 2.15" X 2.15"
SCX-X-40K	X	944LM	4000K	3.35" X 2.75" X 2.15" X 2.15"
SCX-X-50K	X	1037LM	5000K	3.35" X 2.75" X 2.15" X 2.15"
SCX-IC-30K	INSIDE CORNER	629LM	3000K	7.25" X 7.25" X 3.35" X 2.75"
SCX-IC-35K	INSIDE CORNER	726LM	3500K	7.25" X 7.25" X 3.35" X 2.75"
SCX-IC-40K	INSIDE CORNER	787LM	4000K	7.25" X 7.25" X 3.35" X 2.75"
SCX-IC-50K	INSIDE CORNER	854LM	5000K	7.25" X 7.25" X 3.35" X 2.75"



JOB NAME: _____

DATE: _____

TYPE: _____



FACTORY-INSTALLED OPTIONAL ACCESSORIES:

LOUVER VERSION




MODEL	DESCRIPTION	SIZE	LUMENS @ 4000K
OPT-SCX-LUV-6FT	Louver include lens inside	6FT	6480LM

INDIRECT (UP) LIGHTING




MODEL	WATTS	LUMENS	COLOR TEMP	SIZE
OPT-SCX-ULM-6FT-24W-30K	24W	2400LM	3000K	6FT
OPT-SCX-ULM-6FT-24W-35K	24W	2472LM	3500K	6FT
OPT-SCX-ULM-6FT-24W-40K	24W	2520LM	4000K	6FT
OPT-SCX-ULM-6FT-24W-50K	24W	2592LM	5000K	6FT

COLOR OF YOUR CHOICE



MODEL	DESCRIPTION	SIZE
OPT-SCX-CLR-6FT	Add this option and specify your desired color on your purchase order or provide a swatch to match. For painted flanged fixture or optional rod mounting set please also add the relevant option below for each fixture	6FT

EMERGENCY BATTERY BACKUP



MODEL	DESCRIPTION	SIZE
OPT-EM-CM1INT	Add this option for 90-minute battery backup installation. If ordering a series of this fixture to link call us or specify on your purchase order on which fixture to install the backup and where you would like the test buttons	6FT

ULTRASONIC BI-LEVEL MOTION SENSOR

MODEL	DESCRIPTION
OPT-SCX-SEN2US	This option installs an advanced motion sensor that will turn the lights on when the area is occupied. When the area is cleared, after a preset hold time of 5 sec or more the lights are dimmed to a standby level of 30% or more. If still no motion is detected, after the standby period, the light are turned off. All setting are programmable with a remote control
OPT-SCX RC	Optional remote control for sensor


LINKING

MODEL	DESCRIPTION
OPT-SCX-LINKWIRING	FIXTURES ARE EQUIPED WITH PRE-INSTALLED LINKING BRACKETS AND ACCESSORIES AND ONLY NEED TO BE WIRED TOGETHER. TO RECEIVE A FIXTURE PREWIRED FOR LINKING, ORDER THE OPTION BELOW FOR EACH LINK TO ANOTHER FIXTURE OR TO A CORNER MODULE.



MOUNTINGS & OPTIONAL ACCESSORIES:


SURFACE MOUNTING



YOU DO NOT NEED TO ORDER ANY ACCESSORIES.


SCREW AND ANCHOR KIT PROVIDED WITH EACH FIXTURE CAN BE USED TO FASTEN THE FIXTURE DIRECTLY TO THE HARD SURFACE THROUGH THE HOLES ON TOP OF THE FIXTURE.

WALL MOUNTING




MODEL	DESCRIPTION	SIZE
OPT-SCX-WM-6FT	ORDER THIS OPTION AND WALL MOUNTING BRACKETS WILL BE INSTALLED ON BACK OF FIXTURE. CONNECTION CABLES WILL ENTER THE FIXTURE THROUGH ONE OF THESE WALL-MOUNTING BRACKETS. ON YOUR PURCHASE ORDER SPECIFY THE POSITION OF YOUR WIRE ENTRY FROM THE WALL AND THE BRACKETS WILL BE INSTALLED ON THE BACK ACCORDINGLY.	6FT

RECESSED MOUNT WITH FLANGE



MODEL	DESCRIPTION	SIZE
OPT-SCX-FMR-6FT	ORDER THIS OPTION AND THE FIXTURE WILL BE EQUIPPED WITH A 1/2" WIDE FLANGE ON FOUR SIDES. ADVANCED DESIGN TOGGLE STYLE BRACKETS WILL ALSO BE PROVIDED, TO ADJUST AND HOLD THE FIXTURE AGAINST DRYWALL OR OTHER HARD CEILING FROM THE TOP. WHEN LINKING TO ANOTHER FIXTURE OR CORNER MODULE, CALL US OR SEND A COPY OF YOUR PLAN ALONG WITH YOUR PO AND FLANGES WILL BE REMOVED ON THOSE ENDS THAT NEED	6FT

FLANGELESS RECESS MOUNT IN DRYWALL (MUD-IN)



MODEL	DESCRIPTION	SIZE
OPT-SCX-MIF-6FT	ORDER THIS OPTION AND THE FIXTURE WILL BE EQUIPPED WITH MUD-IN BRACKETS ON ALL FOUR SIDES, MOUNTED AT 1/16" FROM THE LENS SURFACE (SPECIFY IF OTHER SPACING IS NEEDED). ADVANCED DESIGN TOGGLE STYLE BRACKETS WILL ALSO BE PROVIDED, TO ADJUST AND HOLD THE FIXTURE AGAINST DRYWALL CEILING FROM THE TOP. WHEN LINKING TO ANOTHER FIXTURE OR CORNER FIXTURE MODULE CALL US OR SEND A COPY OF YOUR PLAN ALONG WITH YOUR PO AND FLANGES WILL BE REMOVED ON THOSE ENDS THAT NEED TO MAKE A SEAMLESS CONNECTION.	6FT

SUSPENDED MOUNTING ACCESSORIES (NOT INCLUDED)



YOU DO NOT NEED TO ORDER ANY ACCESSORIES.

MAKE RECESSED PREPARATIONS BY INSTALLING A HORIZONTAL PLANK OF WOOD ON TOP OF THE WOOD CEILING AT RECESSED HEIGHT OF 3-3/8".

SCREW AND ANCHOR KIT PROVIDED WITH EACH FIXTURE CAN BE USED TO FASTEN THE TOP OF THE FIXTURE TO THE WOOD PLANK THROUGH THE HOLES ON TOP OF THE FIXTURE.

YOU CAN ALSO INSTALL VERTICAL WOOD BOARDS ON TOP OF THE CEILING AT THE EDGE OF THE OPENING AND OPEN THE FIXTURE AND PUT SCREWS THROUGH THE SIDES OF THE FIXTURE HOUSING TO FASTEN IT TO THE WOOD BOARDS.



JOB NAME: _____

DATE: _____

TYPE: _____

MOUNTINGS & OPTIONAL ACCESSORIES:

SUSPENDED MOUNTING ACCESSORIES (NOT INCLUDED)



SCL-CS

SCL-CS3



SCL-6FT-SJTW18/5



SCL-6FT-SJTW18/5-100FT



SCL-6FT-SJTW18/5-100FT-BK




SCL-6FT-SJTW18/6-100FT



SCL-ASC-500FT

SUSPENSION ROD KITS



MODEL	No. OF PAIR	SIZE
SCL-RS-12	2	12 INCH
SCL-RS-24	2	18 INCH
SCL-RS-36	2	24 INCH
SCL-RS-48	2	48 INCH

MODEL	DESCRIPTION
SCL-CS	ADJUSTABLE 6FT 1/16" AIRCRAFT CABLE SUSPENSION KIT WITH CANOPY FOR CEILING OR T-BAR.
SCL-CS3	ADJUSTABLE 6FT 1/16" AIRCRAFT CABLE SUSPENSION KIT WITH CANOPY FOR CEILING OR T-BAR
SCL-6FT-SJTW18/5	6FT WHITE CORD, SJTW 18 AWG 5-CONDUCTOR (BLACK, WHITE, GREEN + PURPLE & GRAY FOR 0-10V DIMMING)
SCL-6FT-SJTW18/5-100FT	100FT ROLL OF WHITE CORD, SJTW 18 AWG 5-CONDUCTOR (BLACK, WHITE, GREEN + PURPLE & GRAY FOR 0-10V DIMMING)
SCL-6FT-SJTW18/5-100FT-BK	100FT ROLL OF BLACK CORD, SJTW 18 AWG 5-CONDUCTOR (BLACK, WHITE, GREEN + PURPLE & GRAY FOR 0-10V DIMMING)
SCL-6FT-SJTW18/6-100FT	100FT ROLL OF WHITE CORD, SJTW 18 AWG 6-CONDUCTOR (BLACK, WHITE, GREEN + PURPLE & GRAY FOR 0-10V DIMMING + RED FOR BACKUP INVERTOR)
SCL-ASC-500FT	1/16" 500 FT. STEEL AIRCRAFT SUSPENSION CABLE

