



**SL-20W-50K-BZ**  
**SL-20W-30K-BZ**  
**SL-20W-50K-WH**  
**SL-20W-30K-WH**

**LED SECURITY LIGHTS**

Ideal for doorway, pathway and alleys. Great for use with optional motion sensors or photocell.

**ELECTRICAL SPECIFICATIONS:**

- Voltage: 120VAC, 50/60Hz
- Wattage: 20W
- Power Factor: 0.90~0.97
- Efficacy: 100LM/W

**HOUSING SPECIFICATIONS:**

- Housing: Die-cast aluminum with powder coat finish
- Fits on a 4" weatherproof box, flush mounts on wall over a junction box or plaster ring, or over a 3" pancake box
- Operating Temperature: -40°F~104°F
- IP Rating: IP65, Suitable for wet locations

**CERTIFICATIONS: ETL**



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
SL-20W-50K-BZ	20W	120VAC	2000LM	5000K
SL-20W-30K-BZ	20W	120VAC	2000LM	3000K
SL-20W-50K-WH	20W	120VAC	2000LM	5000K
SL-20W-30K-WH	20W	120VAC	2000LM	3000K

**OPTIONAL PHOTOCELL:**



SL-PC

MODEL	DESCRIPTION
SL-PC	120V AC, Optional Photocell Component for the above series security lights, Incl. WH & BR trims to match security light color

**LIGHTING SPECIFICATIONS:**

- Cover Type: clear lens
- Total lumens: 2000LM
- Color temperature: 5000K/3000K
- Color rendering index: 80
- Light Beam Angle: 100°

**WARRANTY: 7 years**

