



- SL-20W-50K-BZ-D**
- SL-20W-30K-BZ-D**
- SL-20W-50K-WHT-D**
- SL-20W-30K-WHT-D**

LED SECURITY LIGHTS

Ideal for doorway, pathway and alleys. Great for use with optional motion sensors or photocell.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120VAC, 50/60Hz
- Wattage: 20W
- Power Factor: 0.90~0.97
- Efficacy: 120LM/W

HOUSING SPECIFICATIONS:

- Housing: Die-cast aluminum with powder coat finish
- Mounts flush on wall or 4" round weatherproof box
- Can be installed with any standard LED dimmers (TRIAC types)
- Operating Temperature: -40°F~104°F
- IP Rating: IP65, Suitable for wet locations

CERTIFICATIONS: ETL



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
SL-20W-50K-BZ-D	20W	120VAC	1900LM	5000K
SL-20W-30K-BZ-D	20W	120VAC	1900LM	3000K
SL-20W-50K-WHT-D	20W	120VAC	1900LM	5000K
SL-20W-30K-WHT-D	20W	120VAC	1900LM	3000K

OPTIONAL MOTION SENSERN & PHOTOCELL:



SL-PIR-WH SL-PIR-BZ SL-HPIR-WH SL-HPIR-BZ SL-PC

MODEL	DESCRIPTION
SL-PIR-WH	120V AC, 180°, 200W Max Load, OUTDOOR MOTION SENSOR (WHITE)
SL-PIR-BZ	120V AC, 180°, 200W Max Load, OUTDOOR MOTION SENSOR (BRONZE)
SL-HPIR-WH	120V AC, 240°, 500W Max Load, OUTDOOR MOTION SENSOR (WHITE)
SL-HPIR-BZ	120V AC, 240°, 500W Max Load, OUTDOOR MOTION SENSOR (BRONZE)
SL-PC	120V AC, Optional Photocell Component for the above series security lights, Incl. WH & BR trims to match security light color

LIGHTING SPECIFICATIONS:

- Dimming: Dimmable
- Cover Type: clear lens
- Total lumens: 1900LM
- Color temperature: 5000K/3000K
- Color rendering index: 80
- Light Beam Angle: 120°

WARRANTY: 7 years

