

SL-28W-MCT-BZ-D

LED DIMMABLE SECURITY LIGHTS



Customer Name:

Project Name:

Note:

Type:



LED Security Light with Triple head, Suitable for Outdoor applications, Ideal for Ideal for doorway, pathway and alleys and Great for use with optional motion sensors or photocell.

8 1/4"(W) x 4 1/4"(H) x 8 11/12"(D)

Features

- 7-Year Warranty
- · Die-cast Aluminum, Powder Coated

Multi-CCT: Selectable Switch is on the bottom of the base

Technical Specifications

Electrical:

Voltage: 120V AC, 50/60Hz

Wattage: 40WPower Factor: >0.9Efficacy: 120 LM/W

Mechanical:

- Die-cast Aluminum, Powder Coated
- Strict Waterproof Treatment Technology, in line with International Waterproof and Dust proof Standards
- Contains no mercury
- Operating Temperature: -40°F~104°F
- Suitable for Wet Location
- 7-Year Warranty

Lighting:

- Multi-CCT: Selectable Switch is on the bottom of the base
- Color temperature: 3000K/4000K/5000K
- Total Lumens: 4800LMColor Rendering index: >80
- Beam Angle: 100°Lifespan: 70000 Hrs.

Applications:

- Ideal for Ideal for doorway, pathway and alleys
- Great for use with optional motion sensors or photocell

Other Model:

• 28W | 2400LM | SL-28W-MCT-BZ-D
















Photometrics: SL-40W-MCT-BZ-D







BUG Rating: B2-U1-G0

Other Views:







Side View

Front View

Back View

Performance Table: SL-40W-MCT-BZ-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
SL-40W-MCT-BZ-D	40W	120-277V	4800LM	3000K 4000K 5000K	B2-U1-G0	120

Sample Ordering

Model	Min. Watt		t C	olor Tem	Housing		Dimming	
SL	_	40W		MCT	_	BZ	_	D

Accessories:

Blank = No Option

SL-PC = 120VAC, UL-RECOG MINIATURE PHOTOCELL "FOR SL SERIES ONLY" 100W Max Load SL-PIR-BZ = 180° 350W Max Load, MOTION SENSOR (WHITE OR BRONZE) WITH LONG ARM CAN BE USED WITH ALL OUTDOOR FIXTURES

 $\mbox{SL-HPIR-BZ}$ = 240° 350W Max Load, MOTION SENSOR (WHITE OR BRONZE) CAN BE USED WITH ALL OUTDOOR FIXTURES

Accessories:



Example:

1. SL-40W-MCT-BZ-D

(For SL 40W 5000K MCT fixture 120V-277V)

2. SL-40W-MCT-BZ-D SL-PC (For SL 40W 5000K MCT fixture 120V-277V)
(120VAC, UL-RECOG MINIATURE PHOTOCELL "FOR SL SERIES ONLY" 100W Max Load)



