


JOB NAME:	
DATE: _	
TYPE: _	

DIMENSIONS:



	MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
	SLE-A-12V-MCT-PIR-WH	3W	12V AC	150LM	MCT
	SLE-A-12V-MCT-PIR-ORB	3W	12V AC	75LM	мст



SLE-A-12V-MCT-PIR-WH SLE-A-12V-MCT-PIR-ORB



Ideal for recessed step lighting, walkway and path lighting, courtyard lighting and deck lighting. Optional face plates sold separately.

ELECTRICAL SPECIFICATIONS:

Voltage: 12V ACWattage: 3W

• Efficacy: 25LM/W~50LM/W

HOUSING SPECIFICATIONS:

- polycarbonate housing
- White or Oli-Rubbed Bronze or Brushed Nickel Finish
- PIR Motion Sensor & Photocell Included
- · Frosted inside of glass lens
- Operating temperature: -40°F ~ 104°F
- Lifespan: 50000 Hrs.
- IP rating: IP65, Wet Locations

CERTIFICATIONS:





LIGHTING SPECIFICATIONS:

- LED type: Integrated SMD LED Module
- Total lumens: 150LM/75LM
- Color temperature: 3000K/4000K/5000K
- Beam angle: 120°

WARRANTY: 3 years

