

STL4 SERIES OUTDOOR LIGHTING

STL4-80-200W-30K-480V

STL4-80-200W-50K-480V


MP Multi Power/Wattage (Selectable)

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



This outdoor lighting is ideal for general site lighting, street, roadway, alleys, loading docks, doorway, pathway, and parking areas

9 1/4"(H) x 23 1/4"(W) x 4 3/4"(D)

Features

- Light Grey Finish
- With NEMA twist-lock Photocell Socket (Shorting Cap included)
- 7-Year Warranty
- Outdoor Light

Technical Specifications

Electrical:

- Voltage: 480V; 60Hz AC
- Power Factor: >0.95
- Wattage: 80W/100W/150W/200W
- Efficacy: 140LM/W

Mechanical:

- Die-cast Aluminum with Powder Coat Finish (Light Grey)
- Cord Type: 40" SJTW 18/3 AWG Cable
- With 2-15/16" Diameter Pole Entry with Adapter Bracket Inside for Smaller Pole Diameters
- Maximum Ambient Temperature: 104°F
- IP Rating: IP65, Suitable For Wet Location
- 7-Year Warranty

Lighting:

- MP: Multi-Power Switch Is Located On The Back Of The Fixture
- Lens Type: Optical TYPE III Lens, High Light Transmittance PC, Anti-UV and Flame Resistant
- Dimming: 0-10 Dimming
- Driver Located in Isolated Compartment for Improved Thermal Management
- Total Lumens: 28000LM Max.
- Color Temperatures: 3000K/5000K
- Color Rendering Index: CRI ≥ 70
- Rated Life: 70,000 hrs

Applications:

- Ideal for general site lighting, street, roadway, alleys, loading docks, doorway, pathway and parking areas



Other Models:

• 50W | 7250LM | STL4-15-50W-30K-480V
• 50W | 7250LM | STL4-15-50W-50K-480V


• 100W | 14500LM | STL4-30-100W-30K-480V
• 100W | 14500LM | STL4-30-100W-50K-480V



Photometrics: STL4-80-200W-480V



BUG Rating: B3-U0-G3



Area 55'x 100' Mounting Height: 9'


Other Views:



Side View
(Shown With Slip Fitter)



Front View
(Shown With Slip Fitter)



Back View
(Shown With Slip Fitter)

Performance Table: STL4-80-200W-480V

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
STL4-80-200W-30K-480V	80W 100W 150W	480V	11200LM 14000LM 21000LM	3000K	B3-U0-G3	140
STL4-80-200W-50K-480V	200W		28000LM	5000K		

Sample Ordering

Model	Min. Watt	Max. Watt	Color Temp.	Volt
STL4	80	200W		480V

30K = 3000K
50K = 5000K

Accessories:

Blank = No Option For Accessories
PC-TWIST = 1800W TUNGSTEN TWIST LOCK PHOTOCELL
STL4-SF = SLIP FITTER FOR POLES UP TO 2-3/4" O.D

Factory-Installed Options

Blank = No Option
OPT-STL-SH-CW = Half shroud option
OPT-STL-SH-FG = Full glare shroud option

ACCESSORIES:



PC-TWIST-480V
1800W TUNGSTEN TWIST LOCK PHOTOCELL



STL4-SF
SLIP FITTER FOR POLES UP TO 2-3/4" O.D

FACTORY-INSTALLED OPTION:



OPT-STL-SH-CW
HALF SHROUD OPTION



OPT-STL-SH-FG
FULL-GLARE SHROUD OPTION

