WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

JOB NAME: _____

DATE: _____

TYPE: _____



DIMENSIONS:

4' LONG, G-13 BASE



Works with A/C Direct (120-277V) using (one) end, (both) ends, or by using an electronic ballast.



When powering lamp with A/C direct using both pins on only one end, do not use the above marked end
Use the opposite end

T8-EZ4-HL-15W-50K-C **T8-EZ4-HL-15W-35K-C**
T8-EZ4-HL-15W-50K-F **T8-EZ4-HL-15W-35K-F**
T8-EZ4-HL-15W-40K-C **T8-EZ4-HL-15W-30K-C**
T8-EZ4-HL-15W-40K-F **T8-EZ4-HL-15W-30K-F**

4FT. T8-EZ4-HL 15W LED GLASS TUBE LAMPS

Glass tube provides better transparency and thermal conductivity than plastic. Ideal for offices, showrooms, refrigerators, cove lighting.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 15W
- Power factor: >0.9
- Efficacy: 140 LM/W~145 LM/W

HOUSING SPECIFICATIONS:

- Operating temperature: -4˚F~104˚F
- Lifespan: 50000 Hrs.
- IP Rating: IP20

CERTIFICATIONS: UL, DLC

MODEL	WATTS	MATERIAL	LUMENS	COLOR TEMP
T8-EZ4-HL-15W-50K-C	15W	CLEAR	2200 LM	5000K
T8-EZ4-HL-15W-50K-F	15W	FROSTED	2300 LM	5000K
T8-EZ4-HL-15W-40K-C	15W	CLEAR	2100 LM	4000K
T8-EZ4-HL-15W-40K-F	15W	FROSTED	2200 LM	4000K
T8-EZ4-HL-15W-35K-C	15W	CLEAR	2150LM	3500K
T8-EZ4-HL-15W-35K-F	15W	FROSTED	2200LM	3500K
T8-EZ4-HL-15W-30K-C	15W	CLEAR	2100LM	3000K
T8-EZ4-HL-15W-30K-F	15W	FROSTED	2050LM	3000K

LIGHTING SPECIFICATIONS:

- No UVA Output
- Base type: G13
- Total lumens: 2100~2300LM
- Color temperature: 3000k/3500k/4000K/5000K
- Color rendering index: >80
- Beam angle: 200˚ Frosted Glass / 110˚ Clear Glass

WARRANTY: 5 years

Rev. 2018-05-09

WESTGATE MFG., INC. • Phone (877) 805-2252 • Fax (877) 809-2252