

					WASHING WASHINGTON	
4	WARNING From 1671 or Expension or From 1671	Inglescope budding				
-	A CAUTION					
SU SU REA Only 1	INTERPRETATION OF THE STATE OF	SEULEWENT TDOOR USE crost winned ape luminaries reible futures				
Our	Artist State Common State Commo	ing unless director		-	114610	
	LOW ADCINST POWER WHISH				1	
			Ш	THE SULE		-
			0	981 13V 13V	197	
lacer locari lentra	DO NO SAME PROPERTY OF THE PRO	100 300 100 100 300 100				

TR-600W-MT-SS

MULTI-TAP (12V/13V/14V/15V AC) LAND-SCAPE TRANSFORMERS

ELECTRICAL SPECIFICATIONS:

Voltage: 120V/60HzWattage: 600W MAXOutput Voltage: 120V

HOUSING SPECIFICATIONS:

- Finish: Stainless Steel
- Terminal Blocks: 2
- Suitable for Indoor and Outdoor use
- Dual Protection:

Primary circuit protection: Auto Reset Thermal Circuit Breaker On Core

Secondary circuit protection: (1) 25A Magnetic Circuit Breaker


• IP Rating: IP67, Suitable for Wet Locations

CERTIFICATIONS:









DIMENSIONS:

L 18.1" X W 7.9" X H 7.9"

ACCESSORIES INCLUDED:



6 Foot plug-in cord included with Transformers

MODEL	WATTS	VOLTAGE
TR-600W-MT-SS	600W	120V

ACCESSORIES (Not Incl.):







TR-MTMR

TR-DTMR

TR-PC

MODEL	DESCRIPTION	
TR-MTMR	24-Hour 3-Prong Mechanical Plug-in Timer	
TR-DTMR	7-Day 3-Prong Digital Plug-in Timer	
TR-PC	Photocell with Plug-in Molex Connector	

WARRANTY: 3 years