

UHX SERIES INDUSTRIAL LIGHTING

UHXE-80-150W-MCTP4-SR
POWER AND CCT- ADJUSTABLE UFO HIGHBAY


WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



10" (W) X 2 1/2" (H)

In a aluminium shell designed for heat dissipation, UHXE is IP65 water resistant rated and ideal for general site lighting, alleys, loading docks, doorways, pathways, parking areas, warehouses and storage buildings.

Features

- Waterproof design, suitable for wet locations
- Aluminum Heat Sink, Outdoor Powder Coating Finish
- Optical Lens: PC Materials High Light Transmittance, Anti-UV, Fire-Resistant
- Multi Color Temperature & Multi Power (Selectable Switch Located On The Driver Housing)

Technical Specifications

Electrical:

- Input Wattage: 80W/110W/150W
- Input Voltage: 120-277V 50/60Hz
- Power Factor: >0.9
- THD: <20%
- Efficacy: 140 LPW

Mechanical:

- Aluminum Heat Sink, Outdoor Powder Coating Finish
- Nano Coating Heat Dissipation Technology
- Optical Lens: PC Materials High Light Transmittance, Anti-UV, Fire-Resistant
- Twist-Lock Zhaga Socket Pre-Installed. See Motion Sensor Accessories.
- 3.3' SJTW 18,3 AWG Power Cable
- 3.3' SJTW Dimming Cable
- LED PCB Board: High Conductive, Waterproof, Aging Resistance, salt mist Resistance, Ensure the Safety and Long Lifespan
- Operating temperature: -40°F to 122°F
- IP rating: IP65, Wet Locations
- 5-Year Warranty

Lighting:

- Dimming: 0~10V
- Total Lumens: 21000LM
- Multi Color Temperature & Multi Power (Selectable Switch Located On The Driver Housing)
- Color Temperatures: 3000K/3500K/4000K/5000K
- Color Rendering index: > 80
- Beam Angle: 90°
- Lifespan: 50,000 Hrs

Applications:

- Ideal for general site lighting, alleys, loading docks, doorway, pathway, parking areas, warehouses and storage buildings.

Other Models:

- 150W | 21000LM | UHXE-80-150W-MCTP4-SR-WH




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |




WG-02092022

Photometrics: UHXE-80-150W-MCTP4-SR



BUG Rating: B4-U3-G1



Area 65'x 65' Mounting Height: 9'

Performance Table: UHXE-80-150W-MCTP4-SR

MODEL NO.	Wattage	Voltage	Lumens	Color Temp	BUG Rating	LPW
UHXE-80-150W-MCTP4-SR-WH	80W 110W 150W	120-277V	11200LM 15400LM 21000LM	3000K 3500K 4000K 5000K	B4-U3-G1	140

Sample Ordering

Model Wattage Wattage Color Temp. Sensor Ready

UHX - 80 - 150W - MCTP4 - SR

Accessories:

Blank = No Accessory
 HB-RING = HIGHBAY TOP RING ADAPTER, 1/2in
 HB-EB-50/75 = HIGHBAY EXPANSION BUSHING FROM 1/2in TO 3/4"
 UHX-SMB = UHX SERIES SURFACE MOUNTING YOKE BRACKET
 UHX-SC = UHX SERIES 22" SAFETY CABLE
 UHXE-PCR-A-90D = UHXE 80-150W 90-DEGREE PC REFLECTOR
 UHXE-PCR-A-60D = UHXE 80-150W 60-DEGREE PC REFLECTOR
 UHXE-RPMB = UHXE 3.3 FT. RIGID PIPE STAND WITH TOP CANOPY
 UHX-SA-5075 = 1/2 IN STEM-MOUNTING ADAPTER WITH CABLE PASSAGE WITH 1/2 IN TOP THREAD
 WEC-3MR-72-TLB-BK = 600W Max, ZHAGA 12-24VDC PIR SENSOR, BLACK, WITH BASE (OPTIONAL REMOTE CONTROL WEC-3RC)
 WEC-3MBT-72-TLB-BK = 600W Max, ZHAGA 12-24VDC PIR SENSOR, BLACK, WITH BASE (OPTIONAL REMOTE CONTROL WEC-3RC)
 UHXE-PCC-A = UHXE-80-150W BOTTOM COVER FOR PC REFLECTOR, FITS BOTH 60D 90D

Factory-Installed Option:

Blank = No Accessory
 OPT-EM-UHX = EXTERNAL EMERGENCY BACKUP BATTERY INSTALLED ON TOP OF THE FIXTURE
 OPT-HBC=125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V, 16/3TL, WHITE
 OPT-HBC=277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V, 16/3TL, WHITE
 OPT-HBC=125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A, 125V, 18/3TL, WHITE
 OPT-SEN-UHX = MICROWAVE BI-LEVEL SENSOR

ACCESSORIES:



UHXE-PCC-A
 UHXE-80-150W Bottom
 Cover For Pc Reflector,
 Fits Both 60D 90D

FACTORY-INSTALLED OPTION:



OPT-EM-UHX
 EXTERNAL EMERGENCY
 BACKUP BATTERY INSTALLED
 ON TOP OF THE FIXTURE
 (The bracket can be painted)



OPT-SEN-UHX
 MICROWAVE BI-LEVEL
 SENSOR



ACCESSORIES:



HB-RING
HIGHBAY TOP RING
ADAPTER, 1/2in



HB-EB-50/75
HIGHBAY
EXPANSION
BUSHING FROM 1/2in
TO 3/4"



UHX-SMB
UHX SERIES SURFACE
MOUNTING YOKE
BRACKET



UHX-SC
UHX SERIES 22"
SAFETY CABLE



UHX-SA-5075
1/2 IN STEM-MOUNTING
ADAPTER WITH CABLE
PASSAGE WITH 1/2 IN TOP
THREAD



UHXE-RPMB
UHXE 3.3 FT. RIGID PIPE
STAND WITH TOP CANOPY



UHXE-PCR-A-90D
UHXE-80-150W 90-DEGREE
PC REFLECTOR



UHXE-PCR-A-60D
UHXE-80-150W 60-DEGREE
PC REFLECTOR



WEC-3MR-72-TLB-BK
WEC-3MBY-72-TLB-BK
600W Max, ZHAGA 12-24VDC PIR
SENSOR, BLACK, WITH BASE
(OPTIONAL REMOTE CONTROL
WEC-3RC)

FACTORY-INSTALLED OPTION:



OPT-HBC-125SB-BK
STRAIGHT BLADE PLUG 10FT, 15A,
125V, 18/3TL, BLK



OPT-HBC-125TL-BK
NEMA TWIST-LOCK PLUG 8FT, 15A,
125V, 16/3TL, BLK



OPT-HBC-277TL-BK
NEMA TWIST-LOCK PLUG 8FT, 15A,
277V, 16/3TL, BLK

