



JOB NAME: _____

DATE: _____

TYPE: _____



DIMENSIONS:

16.4'(L) x 0.5"(W)

MODEL	WATTS PER FT.	VOLTAGE	LUMENS PER FT.	COLOR TEMP	REEL LENGTH	MAX RUN
ULR-OT-16F-HO-RGBW	5.8W	24VDC	225LM	RGB	16.4FT.	16.4FT.

OPTIONAL ACCESSORIES:



ULR-IN-HO-RDBW-COUP-6I-WR
ULR-IN-HO-RDBW-COUP-3F-WR



ULR-IN-HO-RDBW-COUP-NO-WR



ULR-IN-HO-RDBW-CONN-6I-WR
ULR-IN-HO-RDBW-CONN-3F-WR

MODEL	DESCRIPTION
ULR-IN-HO-RDBW-COUP-6I-WR	Coupling to connect 2 high output ribbons, 6"
ULR-IN-HO-RDBW-COUP-3F-WR	Coupling to connect 2 high output ribbons, 3'
ULR-IN-HO-RDBW-COUP-NO-WR	Coupling to connect 2 high output ribbons, no wire
ULR-IN-HO-RDBW-CONN-6I-WR	Power feed cable to connect high output ribbon to
ULR-IN-HO-RDBW-CONN-3F-WR	Power feed cable to connect high output ribbon to power, 3'

LIGHTING SPECIFICATIONS:

- Dimming: Dimmable using a magnetic driver
- LED: SMD5050RGBW chip spaced 5/8" on center, 19 per foot, 0.31 watts each
- LED Type: SMD2216
- Total lumens: 225LM per ft.
- Color temperature: RGB
- Color rendering index: 90
- Beam Angle: 120°

WARRANTY: 5 years

ULR-OT-16F-HO-RGBW

24V OUTDOOR HIGH OUTPUT RGBW LED RIBBON

Ideal for undercabinet, soffit, display cases and toe kick lighting.

ELECTRICAL SPECIFICATIONS:

- Voltage: 24VDC (LED driver required)
- Wattage: 5.8W per ft.
- Max Run: 16.4ft.

HOUSING SPECIFICATIONS:

- Cutting increment: Every 4 inches
- Red 3M VHB double sided adhesive
- Includes (connected 1 female ribbon-to-power supply connector) and 1 male plug for connection to next ribbon
- Suitable for Wet Locations

CERTIFICATIONS: UL

