



JOB NAME: _____

DATE: _____

TYPE: _____

DIMENSIONS:

Dimensions: 24cm x 48cm / 9.45 inches x 18.90 inches

ULS-2448-35W-30K
 ULS-2448-35W-40K
 ULS-2448-35W-50K

24V LED FLEXIBLE SHEET

Ideal for undercabinet, soffit, display cases and toe kick lighting.

ELECTRICAL SPECIFICATIONS:

- Voltage: 24VDC (LED driver required)
- Wattage: 35W
- Max current per run: ~5A Safe limit is about 3 sheets (~3.72 sq ft)

HOUSING SPECIFICATIONS:

- 3M double sided tape(9474LE) is preinstalled
- Operating Temp: -4° to 104°F
- IP rating: IP20

CERTIFICATIONS: UL



MODEL	WATTS PER FT.	VOLTAGE	COLOR TEMP	DIMENSION
ULS-2448-35W-30K	35W	24V	3000K	9.45" X 18.90"
ULS-2448-35W-40K	35W	24V	4000K	9.45" X 18.90"
ULS-2448-35W-50K	35W	24V	5000K	9.45" X 18.90"

LIGHTING SPECIFICATIONS:

- Dimming: Dimmable using a magnetic driver
- LED Type: SMD2835
- Color temperature: 3000K/4000K/5000K
- Color rendering index: 90
- Beam Angle: 120°

CUT POINT MEASUREMENTS (CENTER TO CENTER):

Horizontal cuts (along the 48cm / 18.9" side):

- ~12cm (4.72") from the left edge to the first cut
- ~24cm (9.45") from the left edge to the center
- ~36cm (14.17") from the left edge to the third cut

Vertical cuts (along the 24cm / 9.45" side):

- ~8cm (3.15") from the top edge to the first cut
- ~16cm (6.3") from the top edge to the second cut

WARRANTY: 5 years

