

WAX SERIES

Outdoor Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

WAX-20-40W-MCTP-BK


MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas. Great for use with motion sensors or another instant on/off controls.

14" (W) x 12 8/9" (H) x 5 1/4" (D)

Features

- High Light Transmittance, Anti-UV and Fire Resistant PC Lens
- Two 1/2" Knockouts on Each Side
- Die-Cast Aluminum With Powder Coat Finish
- 7-Year Warranty
- Multi CCT and Power (Switches are inside fixture)

Technical Specifications

Electrical:

- Voltage: 120-277V AC 60Hz
- Wattage: 20W/30W/40W
- Power Factor: >0.9
- THD: <20%
- Efficacy: 140 LPW

Mechanical:

- Die-Cast Aluminum With Powder Coat Finish
- High Light Transmittance, Anti-UV and Fire Resistant Shatterproof PC Lens
- DC Button Photocell with ON/OFF switch Included
- Light Head Can Be Adjusted From 0° to 90°
- Full Cutoff, Dark Sky Compliant
- Two 1/2" Knockouts on Each Side
- Operating Temperature: -40°F -113°F
- 7-Year Warranty
- IP65, Suitable For Wet Location

Lighting:

- Dimming: 0~10V Dimmable
- Multi CCT and Power (Switches are inside fixture)
- Lumileds 2835, High CRI.
- Total Lumens: 5600LM Max
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: H127° x V85°
- Rated life: 70,000 Hrs

Applications:

- Entrance Lighting
- Courtyard Lighting
- Industrial Lighting
- Outdoor Landscape Lighting
- Building The hotel
- Wall Lighting Area And So On





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |




WG-ZY-24-2Z

Photometrics: WAX-20-40W-MCTP-BK



BUD Rating: B3-U3-G3



Area 75'x 75' Mounting Height: 8'

Other Views:



Side View



Front View



Bottom View

Performance Table: WAX-20-40W-MCTP-BK

MODEL NO.	t @ P	s } o š P	> μ u v •	} o } CE d u % o XZ Ÿ v PLPW		
WAX-20-40W-MCTP-BK	20W	120~277V	2800LM	3000K 4000K 5000K	B3-U3-G3	140
	30W		4200LM			
	40W		5600LM			

Sample Ordering

Model	Min.	Wattage	Color Temp.	House				
WAX	-	20	-	40W	-	MCTP	-	BK

Factory-Installed Option:

Blank = No Option For Accessories
 OPT-EM-WAX-40 = INTERNAL EMERGENCY BACK UP BATTERY
 OPT-SEN-3MRLV-5 = PROGRAMMABLE MICROWAVE SENSOR
 OPT-WP-480V = CHANGE VOLTAGE TO 480V
 OPT-CLR-85(BK/GR/SR/WH) = PAINT
 OPT-CLR-MC (260 SET UP PRICE FEE PER PROJECT) = PAINT
 OPT-TRS-T20 = TAMPER RESISTANT

FACTORY-INSTALLED OPTION:



OPT-EM-WAX-40



OPT-SEN-3MRLV-5



COLOR CHART: * Choose from one of our Premium Colors with no set-up fee.

Gloss:



SILVER METALLIC
70 GLOSS
T357-GR105



SILVER METALLIC
30 GLOSS
T353-GR06

DARK RED 90
GLOSS
P009-RD02

INTERNATIONAL
ORANGE 90
GLOSS
T009-OG26

SAFETY ORANGE
90 GLOSS
T009-OG01

YELLOW 90
GLOSS
T009-YL14

YELLOW 90
GLOSS
T009-YL01



RAL 8028 TERRA
BROWN 90 GLOSS
C209-BR358

TRAFFIC GREEN
70 GLOSS
T007-GN16

GREEN 70 GLOSS
T007-GN13

GREEN 60 GLOSS
C006-GN03

BLUE 90 GLOSS
T009-BL01

DARK BLUE 80
GLOSS
T008-BL20

Hammer:




WHITE HAMMER
T013-WH09



BEIGE HAMMER
T013-BG38



GREY HAMMER
C013-GR08



SILVER
HAMMERTONE
T064-GR05


BLACK HAMMER
T013-BK62




RED HAMMER
T013-RD15



GREEN HAMMER
T013-GN220



BLUE HAMMER
T013-BL468



BRONZE HAMMER
T012-BR161


Texture:



WHITE TEXTURE
C031-WH120



FLINT GRAY
TEXTURE
T243-GR522



BLACK TEXTURE
C241-BK109



RED TEXTURE
T241-RD129




BLUE TEXTURE
C241-BL544




OIL RUBBED
BRONZE TEXTURE
T291-BR251


Vein:



BLACK/WHITE
VEIN
T075-WH34



SILVER VEIN
T375-BK26



COPPER VEIN
EXTERIOR
T075-BK211



GOLD VEIN
T375-BK10



COPPER VEIN
T375-BK07

