

WPMAX SERIES

LED OUTDOOR LIGHTING

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

WPMAX-25-40W-MCTP
WPMAX-25-40W-MCTP-BK
WPMAX-25-40W-MCTP-SIL


MAX-FEATURE WALL PACK, LENS TYPE SELECTABLE TYPE 2, 3, 4
MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)

Customer Name: _____


Project Name: _____

Note: _____

Type: _____



Avail. Finishes:



8.3"(W) x 6.69"(H) x 5.43"(D)

A durable and energy-efficient outdoor lighting solution, designed with a cutoff lens to minimize glare and light pollution. Ideal for enhancing security and visibility in commercial, industrial, and residential applications while maintaining compliance with dark-sky regulations.

Features

- ADC12 Aluminum Heat Sink, Outdoor Powder Coating
- Multi Color Temperature & Multi Power/Wattage (Switches are inside fixture)
- Adjustable throw (Narrow, Medium & Wide)
- Prismatic Borosilicate Glass Lens
- Photocell included

Technical Specifications

Electrical:

- Input Wattage: 25W/30W/40W
- Input Voltage: 120-277V AC 50/60Hz
- Input current: 0.6A
- Power factor: >0.9
- Efficacy: 135 LPW

Mechanical:

- ADC12 Aluminum Heat Sink, Outdoor Powder Coating
- Photocell included
- Lens: Prismatic Borosilicate Glass Lens
- Same Footprint as Traditional HID Wall Packs
- Four 1/2" Hubs: 1 top, 1 on Each Side, 1 Rear
- Mounting: Wall Mounting
- Operating Temperature: -40°F ~ 122°F
- IP rating: IP65, Wet Locations
- 7-Year Warranty

Lighting:

- Multi Color Temperature & Multi Power/Wattage (Switches are inside fixture)
- Dimming: 0-10V Dimming
- Multi Power & CCT (Switches are inside fixture)
- Adjustable throw (Narrow, Medium & Wide)
- Total Lumens: 5400LM Max.
- Color Temperature: 3000K/4000K/5000K
- CRI: >70
- Lifespan: 70000 Hrs.


Applications:

- Entrance lighting, courtyard lighting;
- Industrial lighting, Outdoor landscape lighting;
- Building, The hotel;
- Wall lighting area and so on.



Photometrics: WPMAX-25-40W-MCTP


T2: BUG rating



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires


BUG Rating: B2-U0-G1

Iso-illuminance plot



Area 24'x 24'


T3: BUG rating



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires


BUG Rating: B2-U0-G1

Iso-illuminance plot



Area 24'x 24'


T4: BUG rating



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG Rating: B2-U0-G1

Iso-illuminance plot



Area 24'x 24'



Other Views:


Bronze:



Side View



Front View



Back View


Black:



Side View




Front View



Back View

Silver:



Side View



Front View



Back View

Performance Table: WPMAX-25-40W-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
WPMAX-25-40W-MCTP	20W	120-277V	2700LM	3000K	B2-U0-G1	135
WPMAX-25-40W-MCTP-BK	30W		4050LM	4000K		
WPMAX-25-40W-MCTP-SIL	40W		5400LM	5000K		

Sample Ordering

Model **Min. Watt** **Max. Watt** **Watt/Color Temp.** **Finish**
 WPMAX - 20 - 40W - MCTP -
Blank = Bronze
BK = Black
SIL = Silver

Factory-Installed Options:

- Blank = No Option For Accessories
- OPT-EM-WPMAX-60 = INTERNAL EMERGENCY BACKUP BATTERY
- OPT-WP-480V = CHANGE VOLTAGE
- OPT-SEN-3MRLV-5 = PROGRAMMABLE MICROWAVE (BI-LEVEL FOR 80W & UP)
- OPT-SEN-NLS-3MRLV-5 = WG NETWORK SENSOR
- OPT-SEN-KEILTON-3MRLV-5 = KEILTON NETWORK SENSOR
- OPT-TRS-T20 = TAMPER RESISTANT SCREW
- PT-PC-B = BUTTON
- OPT-CLR-85(BK/GR/SR/WH) = COLOR PAINT
- OPT-CLR-MC (260 SET UP FEE PER PROJECT) = COLOR PAINT
- WEC-8RC = REMOTE CONTROL

FACTORY-INSTALLED OPTIONS:



OPT-EM-WPMAX-60




WEC-8RC

OPT-SEN-3MRLV-5


Narrow



Medium



Wide



COLOR CHART: * Choose from one of our Premium Colors with no set-up fee.

Gloss:



SILVER METALLIC
70 GLOSS
T357-GR105



SILVER METALLIC
30 GLOSS
T353-GR06



DARK RED 90
GLOSS
P009-RD02



INTERNATIONAL
ORANGE 90
GLOSS
T009-OG26



SAFETY ORANGE
90 GLOSS
T009-OG01



YELLOW 90
GLOSS
T009-YL14



YELLOW 90
GLOSS
T009-YL01



TRAFFIC GREEN
70 GLOSS
T007-GN16



GREEN 70 GLOSS
T007-GN13



GREEN 60 GLOSS
C006-GN03



BLUE 90 GLOSS
T009-BL01



DARK BLUE 80
GLOSS
T008-BL20



RAL 8028 TERRA
BROWN 90 GLOSS
C209-BR358

Hammer:




WHITE HAMMER
T013-WH09



BEIGE HAMMER
T013-BG38



GREY HAMMER
C013-GR08



SILVER
HAMMERTONE
T064-GR05




BLACK HAMMER
T013-BK62



RED HAMMER
T013-RD15



GREEN HAMMER
T013-GN220



BLUE HAMMER
T013-BL468



BRONZE HAMMER
T012-BR161

Texture:



WHITE TEXTURE
C031-WH120



FLINT GRAY
TEXTURE
T243-GR522




BLACK TEXTURE
C241-BK109



RED TEXTURE
T241-RD129



BLUE TEXTURE
C241-BL544




OIL RUBBED
BRONZE TEXTURE
T291-BR251


Vein:



BLACK/WHITE
VEIN
T075-WH34



SILVER VEIN
T375-BK26



COPPER VEIN
EXTERIOR
T075-BK211



GOLD VEIN
T375-BK10



COPPER VEIN
T375-BK07

