15. Stainless Steel Glass Supports

with round tube



System TOP 3535 SBM

Easily adaptable from serve-over version to self-service version




Tip: Suitable lighting covers are on page 402.



- Easily adaptable from serve-over version to self-service version
- With sneeze guard
- Also suitable for granite surfaces
- Made of high-quality stainless steel

With sneeze guard



WIHA TOP 3535 SBM

Name of the item	ArtNo.	Glass shelf		Front panel	
		Glass length	Angle	Glass length	Angle
Support left	2396	+17 mm	90°	-20,5 mm	90°
Support right	2397	+17 mm	90°	-20,5 mm	90°
Central support - 180°	2398	-1 mm	90°	-20,5 mm	90°
Mounting plate (support)	4024				
Retainer set, side panel	2407				

The glass length is based on the centre distance (drilling distance) of the supports. Changing the glass length should be considered for each support on a case-by-case basis

Design

The supports are made entirely of stainless steel, material 1.4301. The surface is matt finished (glass bead blasted). The support is made secure with a mounting plate available as an accessory. The supports are prepared for a cable inlet with duct openings.

The cross-beam has an M5 thread for securing the neccessary side panel. The maximum distance between the supports must not exceed 1250 mm.

If no side glass panel is mounted on the support, the support must be stabilised by a separate support strut!

Special Accessories

Support strut for stabilisation, if no side glass panel is mounted.

The use of support struts is also recommended with central supports. Design: Stainless steel round tube, diameter = 10 mm.

> Art.-No. 2394