for keeping food warm



Snack-Counter STEAM 520 BE SLIDE OUT


Heated display case with pull-out merchandise shelves and adjustable humidity

Toughened Safety Glass Front pane, side panes, upper pane made of toughened safety class

Heated display case with one merchandise area

- Adjustable humidity (6 steps) for optimal product quality
- Fully automatic steam generator with tank/pump system for automatic water filling
- Easy cleaning of the removable humidifier tray
- Good illumination of the merchandise room by a temperature-resistant lighting
- No water connection or drain required
- Basic heat, infrared heat and humidification are each adjustable in 6 steps
- Also available with cutting board (version: 1 cutting board)





- Adjustable humidity (6 steps) for optimal product quality
- Fully automatic steam generator with tank/pump system for automatic water filling
- Easy cleaning of the removable humidifier tray
- Good illumination of the merchandise room by a temperature-resistant lighting
- For the version with tank/pump system: No water connection or drain required
- Also available with a fixed water connection
- Temperature adjustable from 40°C to 75°C, humidification adjustable in 6 steps
- Also available with cutting boards (version: 2 cutting boards)



Fig.: Snack-Counter STEAM BE SLIDE OUT 1 with one display area for merchandise



Fig.: Snack-Counter STEAM BE SLIDE OUT 1.5 with two display areas for merchandise and cutting boards





9. Display Cases – heated

for keeping food warm

Snack-Counter STEAM 520 BE SLIDE OUT 1 with one display area for merchandise	Tank/Pump System					
Serve-over version Height glass top 520 mm	angular	Width [mm]	Depth [mm]	Height Top [mm]	Connection	
Snack-Counter STEAM 520 BE SLIDE OUT 1	33340	491	705	520	230V/1.9 kW	
Snack-Counter STEAM 520 BE SLIDE OUT 1 with cutting board (1 cutting board)	33341	491	705	520	230V/1.9 kW	

Snack-Counter STEAM 520 BE SLIDE OUT 1.5 with two display areas for merchandise	Tank/Pump System	Fixed Water Connection					
Serve-over version Height glass top 520 mm	angular	angular	Width [mm]	Depth [mm]	Height Top [mm]	Connection	
Snack-Counter STEAM 520 BE SLIDE OUT 1.5	33342	33351	587	705	520	230V/1.3 kW	
Snack-Counter STEAM 520 BE SLIDE OUT 1.5 with cutting board (2 cutting boards)	26438	33352	587	705	520	230V/1.3 kW	

Description

Heated display case with circulating air heating for keeping meat products warm. For optimal product quality, the humidity is adjustable in 6 steps.

The steam generator operates fully automatically and includes a tank/pump

system for automatic water filling.

Good illumination of the merchandise room by a temperature-resistant lighting

(warm colour reproduction).

All components are easily accessible for maintenance and cleaning

Commercial product for the installation in stationary food and service counter.

Design

Interior and exterior are made entirely of stainless steel with high-temperature

All visible sides have a ground surface.

All glass panes are made of safety glass.

The steam generator operates fully automatically and is equipped with a tank/pump system and an automatic water filling system. The water tank can be placed under the device in the counter furniture and can be easily removed for

For cleaning, the humidifier tray of the steam generator is easy to remove. It can be cleaned in a dishwasher

The service-friendly controller can be folded down so that all test points are easily

Version "Tank/Pump System"

The water filling of the steam generator is made automatically via a tank/pump system. The water tank can be placed under the device in the counter furniture and can be easily removed for daily filling.

Delivery includes water tank with pump system.

Version "Fixed Water Connection"

The device is equipped with a drain (connection 1 1/4" external thread) and a solenoid valve (3/4" external thread).

Delivery includes water connecting hose 1.5 m; 3/4" for the connection to an on-site water tap.

The drain must be connected by the customer via drain trap and funnel outlet.

Version size 1 (one display area for merchandise)

The heating is made by a powerful large-area heating plate and a powerful quartz radiator with medium and long-wave infrared radiation. The heating plate can be easily folded up for cleaning the interior and is self-holding in the open position. Good illumination by a temperature-resistant LED lighting.

Particularly easy cleaning of the components in the dishwasher, because the guide rails and the ventilation grille can be removed. The pullout is equipped with a large insulated handle and a safety device to prevent it from being pulled out completely. The wing door is hinged on the left as standard. The door hinge can be changed,


the required hinges are included in the scope of delivery. Keep warm temperature > 65°C (at room temperature > 20°C).


Basic heat, infrared heat and humidification can each be adjusted in 6 steps.

Version size 1.5 (two display areas for merchandise) The heating is made by a powerful circulating air blower.

The upper cover plate can be easily folded up for cleaning the interior and is self-holding in the open position.

The wing door is hinged on the left as standard. The door hinge can be changed. Temperature adjustable from 40°C to 75°C.





More drawings are available on www.wiha-web.com under "Info Centre / Customer Area".

