

5. Display Cases – refrigerated

for serve-over



Snack-Counter ECO-Special Size (with insulating glazing)

Made to your measurement instructions



Insulating glazing on all sides.



Made to your measurement instructions!

- **Width, depth and height can be chosen**,
so this display case can be placed, where standard sizes do not fit.
- **Smooth-running sliding doors with rollers**,
easily removable for cleaning.
- **Longer operating life of the cooling unit (LONG-LIFE)**
- **Also suitable for small counter constructions**,
because production is already possible from a depth of 500 mm.
- **No condensation on the glass panes (*)**,
because the construction is entirely made of insulating glass.
- **Energy-saving**
due to the insulating glazing.
- **Temperature range**
< 7°C at 25°C/60% relative humidity
(climate class 3 according to DIN EN ISO 23953).
- **Longer product freshness**
due to a very high humidity.
- **Variable presentation**
by means of continuously height adjustable glass shelves,
which can be set straight or inclined towards the customer.
- **Optionally, with wing door, double wing door or sliding doors**
- **Easy cleaning of the interior area**
by swing-out front glass pane and removable sliding doors.
- **Easy cleaning of the evaporator area**
by liftable evaporator – self-locking per gas pressure springs.

Display case with 2 sliding doors: Art.-No. 12095		
Possible display case dimensions:		
Depth (of the display case):	Width (of the display case):	Height:
500 mm – 680 mm	800 mm – 1600 mm	300 mm – 710 mm
681 mm – 800 mm	600 mm – 1600 mm	300 mm – 710 mm

Price available on request.

Display case with 4 sliding doors: Art.-No. 12094		
Possible display case dimensions:		
Depth (of the display case):	Width (of the display case): *	Height:
500 mm – 680 mm	1601 mm – 2600 mm	300 mm – 710 mm
681 mm – 800 mm	1601 mm – 2600 mm	300 mm – 710 mm

Price available on request.

* From a width of 1600 mm: two-piece front glass and upper glass

For a quotation following information is required:

- Width
- Depth
- Height
- Number of glass shelves
- Design of the doors: wing door right/left; sliding doors; double wing doors

(*) At setpoint 6°/AT 25°C/RH 70%.

Special Accessories

Drain fitting 1 1/4" for connecting to the customer's drain	Art.-No. 3815
Condensate pan, loose	3819
Price label rail glass shelf, special length	11545
Price label rail lower display area	11546

Description

Custom-made refrigerated display case with circulating air for cooling cream cakes, cakes and snacks. On the customer side with angular glass construction made of insulating glass.

The glass shelves are height adjustable and can be set at an angle, which means better presentation.

Temperature: < 7°C at 25°C/60% relative humidity (climate class 3 according to DIN EN ISO 23953).

Commercial product for the installation in stationary food and service counter.

Design

Construction, merchandise display, interior pan and exterior are made entirely of stainless steel, material 1.4301. Pan interior is finished with 1 1/4" flush threaded drain fitting and hygienic corners that are easy to clean.

The insulation is CFC-free. The exterior is made of galvanised sheet steel.

Inside the pan is a generously sized circulating air evaporator with coated surface and quiet low-voltage ventilators (12 V DC) for air circulation. Located above the circulating air evaporator are merchandise displays made of ground stainless steel material 1.4301.

To clean the pan bottom, the merchandise displays can be removed. Afterwards, the circulating air evaporator and the ventilators can be folded upwards and locked in the top position via gas pressure springs.

On the customer side, on the sides and on top with a glass construction made of heat absorbing insulating glazing. The front glass pane on the customer side is mounted in a lower tilting glass holder.

The width, depth, height, the number of glass shelves and the design of the doors (wing door left/right, sliding doors, double wing doors) of the Snack-Counter Special Size are custom-made designed according to the confirmed specifications.

The sliding doors of this display case are equipped with smooth-running and ball bearing mounted rollers.

All upper glass shelves are made of safety glass. For good illumination, a protected LED light (standard colour: white) is mounted above each shelf. The glass shelves are height adjustable several times and can be set at an angle, which means better presentation.

The cooling pan can be easily mounted in the counter recess because of the circumferential mounting lip.

A digital defrosting and temperature controller is mounted beneath the cooling pan. Two air speeds can be selected for different foods. The flat control panel (installation depth: approx. 20 mm) can be removed for mounting in the counter front (cable length: approx. 1 m).

With WIHA-LONG-LIFE for a longer operating life of the cooling unit.

For external cooling unit

Delivery includes:

- Expansion valve for R134a/R513A
- Digital defrost and temperature controller

For ready-to-use cooling unit

The cooling unit is fully pre-assembled and is connected to the cooling pan with refrigerant couplings.

The counter design should include a well-ventilated base unit beneath the cooling pan.

