






SPACING TABLE

Photometric curve	Model Number	Mounting height (m)	Lux level directly under	Anti-panic 0.5 lux				Escape Route 1 lux			
				 Transverse to Wall	 Transverse to Transverse	 Axial to Axial	 Axial to Wall	 Transverse to Wall	 Transverse to Transverse	 Axial to Axial	 Axial to Wall
	DLB1.5-OA2 Open Area lens (125°)	2	6.2	3.8	8.1	8.1	3.8	3.6	7.6	7.6	3.5
		2.5	5.1	4.6	9.8	9.8	4.5	4.1	9.1	9.1	4.0
		3	3.9	5.2	11.3	11.3	5.2	4.5	10.3	10.4	4.4
		3.5	2.7	5.7	12.7	12.8	5.7	4.2	11.3	11.3	4.2
		4	1.6	6.1	14.0	14.1	6.1	2.8	11.3	11.5	2.8
		4.5	1.3	6.5	15.1	15.2	6.4	-	8.3	8.5	-
		5	1.1	5.9	16.1	16.1	5.9	-	7.7	7.8	-
		5.5	0.9	4.4	16.3	16.6	4.6	-	6.8	7.0	-
		6	0.7	-	12.9	13.5	-	-	1.0	-	-
	DLB1.5-C Corridor lens (145°x75°)	2	10.1	-	-	-	-	1.9	4.7	12.1	5.2
		2.5	8.2	-	-	-	-	2.0	5.1	13.7	5.7
		3	6.3	-	-	-	-	2.0	5.4	14.9	6.0
		3.5	4.4	-	-	-	-	2.0	5.6	16.1	4.6
		4	2.5	-	-	-	-	1.8	5.7	15.6	4.2
		4.5	4.4	-	-	-	-	1.6	5.7	15.3	3.8
		5	3.3	-	-	-	-	-	5.6	13.1	-
		5.5	2.2	-	-	-	-	-	5.3	12.0	-
		6	1.1	-	-	-	-	-	4.5	11.0	-
	DLB3-OA2 Open Area lens (125°)	2	10.9	4.0	8.3	8.3	4.0	3.8	8.0	8.0	3.7
		2.5	8.3	4.9	10.1	10.2	4.8	4.5	9.6	9.6	4.4
		3	6.4	5.6	11.9	11.9	5.5	5.1	11.1	11.1	4.9
		3.5	4.6	6.3	13.5	13.5	6.2	5.6	12.5	12.5	5.4
		4	2.7	7.0	15.0	15.0	6.7	6.0	13.7	13.7	5.9
		4.5	2.4	7.5	16.4	16.4	7.3	6.1	14.7	14.7	5.9
		5	2.0	7.9	17.8	17.8	7.7	5.4	15.6	15.6	5.4
		5.5	1.6	8.3	19.0	19.0	8.2	3.7	15.4	15.6	3.7
		6	1.2	8.3	20.1	20.0	8.5	-	10.9	11.4	-
	DLB3-OA1 Open Area lens (155°)	2	6.2	5.2	12.1	12.0	5.1	4.6	10.7	10.6	4.5
		2.5	5.0	6.0	14.0	13.8	5.9	5.2	12.3	12.1	4.9
		3	3.9	6.7	15.7	15.5	6.5	5.4	13.7	13.4	5.0
		3.5	2.7	7.3	17.3	20.0	6.9	3.9	14.8	14.3	4.0
		4	1.5	7.5	18.7	18.4	7.1	1.5	14.0	14.1	1.5
		4.5	1.3	7.5	20.0	19.4	6.7	-	11.8	11.4	-
		5	1.1	5.3	20.9	20.2	5.5	-	9.9	9.7	-
		5.5	0.9	2.5	20.2	20.2	4.7	-	-	-	-
		6	0.7	-	18.2	18.4	-	-	-	-	-
	DLB3-S45 45° Spot lens (45°)	2	161.0	1.1	2.3	2.4	1.1	1.1	2.3	2.4	1.1
		2.5	130.8	1.4	2.9	3.0	1.4	1.4	2.9	3.0	1.4
		3	100.7	1.7	3.5	3.6	1.7	1.7	3.5	3.6	1.7
		3.5	70.5	2.0	4.0	4.2	2.0	2.0	4.0	4.1	2.0
		4	40.3	2.3	4.6	4.8	2.3	2.2	4.6	4.6	2.2
		4.5	34.7	2.5	5.2	5.4	2.6	2.5	5.1	5.1	2.5
		5	29.1	2.8	5.8	5.8	2.8	2.7	5.7	5.7	2.8
		5.5	23.5	3.1	6.3	6.3	3.1	2.9	6.2	6.2	3.0
		6	17.9	3.3	6.9	6.9	3.4	3.2	6.7	6.7	3.2
		6.5	15.0	3.6	7.4	7.4	3.6	3.4	7.2	7.2	3.4
		7	12.2	3.8	7.9	8.0	3.9	3.5	7.7	7.7	3.6